Serie 1423

Ripetitore Ottico-Acustico - Optical and Acoustical Indicator

Dispositivo ad alta luminosità e basso consumo adatto alle più svariate applicazioni per la segnalazione di allarmi, anomalie, stati, ecc.



MODELLO	LED				ALIMENTAZIONE		
	ROSSO	VERDE	GIALLO	BUZZER	24 V	12 V	INCASSO
1423CSA	✓	✓	✓		✓		
1423-12	✓	✓	✓			✓	
1423 BZ	✓	✓		✓	✓		
1423-BZ-12	✓	✓		✓		✓	
1423-BZ-I	✓	✓		✓	✓		✓

Collegamenti	Filo Rosso	Positivo
	Filo Nero	Negativo

Impostazioni	Luce lampeggiante	Ponticello inserito
	Luce fissa	Ponticello disinserito

Specifiche Tecniche	Alimentazione	24 Vcc ±10% / 12 Vcc ±10%
	Corrente	10 ÷ 12 mA [per elemento]
	Corrente Buzzer	12 mA
	Intensità Sonora	75 dB a 50 cm
	Frequenza lampeggio	1 Hz
	Angolo emissione	180º
	Dimensioni	122 x 77 x 34 [115 x 71 x 64 vers. da incasso]
	Materiale corpo	Termoplastico
	Materiale frontale	Alluminio
	Terminali	A filo

Cooper CSA S.r.l. - via San Bovio, 3 - 20054 Segrate (MI)- Italy
Tel: +39 02.959501 - Fax: +39 02.95950598 - www.coopercsa.it

Rif. 08992_03

Serie 1423

Ripetitore Ottico-Acustico - Optical and Acoustical Indicator

Optical and acoustical indicator with LED and
Low current consumption suitable for different applications of alarm, signalling, etc.



MODEL	LED				INPUT VOLTAGE		FLUSH MOUNTING
	RED	GREEN	YELLOW	BUZZER	24 V	12 V	
1423CSA	✓	✓	✓		✓		
1423-12	✓	✓	✓			✓	
1423 BZ	✓	✓		✓	✓		
1423-BZ-12	✓	✓		✓		✓	
1423-BZ-I	✓	✓		✓	✓		✓

Connections	Red cable	+
	Black cable	-

Settings	Blinking	Jumper ON
	Steady	Jumper OFF

Technical Specs	Rated Voltage	24 Vcc ±10% / 12 Vcc ±10%
	Current	10 ÷ 12 mA [each element]
	Buzzer current	12 mA
	Sound pressure level	75 dB @ 50 cm
	Blinking frequency	1 Hz
	Emission angle	180º
	Dimensions	122 x 77 x 34 [115 x 71 x 64 wall mount ver.]
	Housing	Thermoplastic
	Cover	Aluminium
	Terminals	Wired

Cooper CSA S.r.l. - via San Bovio, 3 - 20054 Segrate (MI)- Italy
Tel: +39 02.959501 - Fax: +39 02.95950598 - www.coopercsa.it

Rif. 08992_03