

# Specifications



## Eaton XV-102-E6-57TVRC-10

Eaton XV100 basic (HMI), Second generation CE plastic housing, XSoft-CoDeSys/Galileo OS, Retentive memory, USB host, SmartWire-DT base unit, CANopen communication, 5.7 in TFT resistive touch (VGA) display, Standard blank front bezel

### General specifications

<b>PRODUCT NAME</b>	Eaton XV100 basic human machine interface (HMI)
<b>CATALOG NUMBER</b>	XV-102-E6-57TVRC-10
<b>EAN</b>	7640130097605
<b>PRODUCT LENGTH/DEPTH</b>	11 in
<b>PRODUCT HEIGHT</b>	3.5 in
<b>PRODUCT WIDTH</b>	7.5 in
<b>PRODUCT WEIGHT</b>	1.2 lb
<b>WARRANTY</b>	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
<b>COMPLIANCES</b>	CE Marked RoHS Compliant
<b>CERTIFICATIONS</b>	cULus Listed UL Listed
<b>CATALOG NOTES</b>	All 1xx performance class units have 400MHz processor, 64 MB DRAM, 1x10/100 Ethernet, and 1x USB device.

## Product specifications

<b>BASE UNIT</b>	Retentive memory, USB host, SmartWire-DT
<b>BEZEL</b>	Blank front
<b>COMMUNICATION</b>	CANopen
<b>DISPLAY</b>	5.7 in TFT resistive touch (VGA)
<b>OPERATING SYSTEM</b>	XSoft-CoDeSys Galileo

## Resources

### MULTIMEDIA

[HMI-PLC overview](#)

### SPECIFICATIONS AND DATASHEETS

[Eaton Specification Sheet - XV-102-E6-57TVRC-10](#)

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**



### Eaton Corporation plc

Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

