

# Specifications

Photo is representative

## Eaton RS2-11-C10

Eaton RS-Titan non-contact door interlock safety switch, Magnetic Reed Switch, Polyamide enclosure, 300 mA max DC, 1 Normally Open and 1 Normally Closed, 300 mA at 24 Vdc, 33 Ft. ( 10m ) Cable, < 10% accuracy, 33 Ft. ( 10m )

### General specifications

<b>PRODUCT NAME</b>	Eaton RS-Titan non-contact door interlock safety switch
<b>CATALOG NUMBER</b>	RS2-11-C10
<b>UPC</b>	786685886367
<b>PRODUCT LENGTH/DEPTH</b>	0.94 in
<b>PRODUCT HEIGHT</b>	2 in
<b>PRODUCT WIDTH</b>	0.44 in
<b>PRODUCT WEIGHT</b>	0.875 lb
<b>WARRANTY</b>	1 year
<b>COMPLIANCES</b>	CE Marked
<b>CERTIFICATIONS</b>	UL Listed
<b>CATALOG NOTES</b>	0

## Product specifications

TYPE	Mechanical Limit Switches
CONTACT RATING	300 mA at 24 Vdc
CABLE TYPE	Polyvinyl Chloride (PVC)
ACCURACY	< 10%
ENCLOSURE MATERIAL	Polyamide
CORD LENGTH	396 ft
CONNECTION	33 ft (10m) cable
CONTACT CONFIGURATION	1 NO-1 NC
SWITCH TYPE	Magnetic reed switch
OPERATING TEMPERATURE - MAX	131 °F
OPERATING TEMPERATURE - MIN	14 °F
ENVIRONMENTAL RATING	IP67, IP69K
MAXIMUM DC CURRENT	300 mA

## Resources

### CATALOGS

[Sensing Solutions, Safety Products, Volume 8, Tab 1](#)

### SPECIFICATIONS AND DATASHEETS

[Eaton Specification Sheet - RS2-11-C10](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



### Eaton Corporation plc

Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

