

Specifications

Eaton 1BS102

Eaton Universal fuse block, Modular, 400 A, 150, Celsius, 150, Celsius, Screw, 200 kAIC, Molded black phenolic base, Tin-plated aluminum connector, Zinc-plated steel studs/nut/washer, Stud, 600 V, Used with Type SC fuses, #6-250 kcmil Cu/Al

General specifications

PRODUCT NAME	Eaton Busmann series 1BS10x universal fuse block
CATALOG NUMBER	1BS102
UPC	051712134996
PRODUCT LENGTH/DEPTH	6.6 in
PRODUCT HEIGHT	2.5 in
PRODUCT WIDTH	3.2 in
PRODUCT WEIGHT	0.975 lb
WARRANTY	Not Applicable
COMPLIANCES	Contact factory RoHS Compliant



Powering Business Worldwide

Electrical rating

AMPERAGE RATING 400 A

INTERRUPT RATING 200 kAIC

VOLTAGE RATING 600 V

General information

CONNECTION Screw

MOUNTING METHOD Stud

USED WITH Used with Type SC fuses

Physical details

MATERIAL Tin-plated aluminum connector
Zinc-plated steel studs/nut/washer
Molded black phenolic base

OPERATING TEMPERATURE - MAX 150 °C

OPERATING TEMPERATURE - MIN 150 °C

WIRE SIZE #6-250 kcmil Cu/Al

Resources

CATALOGS [Bussmann series complete full line catalog no. 1007](#)

SPECIFICATIONS AND DATASHEETS [Eaton Specification Sheet - 1BS102](#)

TECHNICAL DATA SHEETS [Bussmann series 1BS102 modular fuse block data sheet no. 1207](#)

TECHNICAL SERVICE BULLETINS [Datasheet - FNQ-30](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.