

Specifications

Photo is representative

Eaton 204979

Eaton Moeller® series STN Control transformer, 0.25 kVA, Rated input voltage 100 – 690 ± 5 % V, Rated output voltage 12 – 250 V

General specifications

PRODUCT NAME	Eaton Moeller® series STN Control transformer
CATALOG NUMBER	204979
MODEL CODE	STN0,25(*/*)
PRODUCT LENGTH/DEPTH	103 mm
PRODUCT HEIGHT	121 mm
PRODUCT WIDTH	106 mm
PRODUCT WEIGHT	2.9 kg
CERTIFICATIONS	CSA-C22.2 No. 66.2-06 UL 506 UL report applies to both US and Canada VDE 0113, VDE 0100 Part 410 VDE 0570 Part 2-2 CSA-C22.2 No. 66 UL Category Control No.: XPTQ2, XPTQ8 UL5085-1 CSA-C22.2 No. 66.1-06 CE Certified by UL for use in Canada IEC/EN 60204-1, ÖVE-EN 13 IEC/EN 61558-2-2 UL 5085-2 UL File No.: E167225 UL Recognized
CATALOG NOTES	Electrical characteristics: all details for no-load loss, short-circuit loss (copper losses), short-circuit voltage and efficiency values relate to a temperature of 20 °C

Product specifications

TYPE	Single-phase STN control transformers
FEATURES	Separate windings Fully Vacuum-impregnated
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product

Resources

APPLICATION NOTES	eaton-transformer-stz-sti-stn-dtz-uti-ap009002-en-us.pdf
BROCHURES	eaton-transformers-brochure-br009002en-en-us.pdf
CATALOGS	eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf
DRAWINGS	eaton-general-control-stn-control-transformer-dimensions-007.eps
ECAD MODEL	ETN.STN0,25(x_x).edz
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - 204979

	standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
AMBIENT OPERATING TEMPERATURE - MAX	40 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
APPARENT POWER	250 VA
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W
NO-LOAD LOSSES	9 W
PRIMARY VOLTAGE 1 - MAX	690 V
PRIMARY VOLTAGE 1 - MIN	100 V
PRIMARY VOLTAGE 10 - MAX	0 V
PRIMARY VOLTAGE 10 - MIN	0 V
PRIMARY VOLTAGE 2 -	0 V

MAX	
PRIMARY VOLTAGE 2 -	0 V
MIN	
PRIMARY VOLTAGE 3 -	0 V
MAX	
PRIMARY VOLTAGE 3 -	0 V
MIN	
PRIMARY VOLTAGE 4 -	0 V
MAX	
PRIMARY VOLTAGE 4 -	0 V
MIN	
PRIMARY VOLTAGE 5 -	0 V
MAX	
PRIMARY VOLTAGE 5 -	0 V
MIN	
PRIMARY VOLTAGE 6 -	0 V
MAX	
CONDUCTOR MATERIAL	Copper
DEGREE OF PROTECTION	IP00
CONNECTION LUG	Yes for > 115 A
CONNECTION TYPE	Terminations, < 115 A
DUTY FACTOR	100 %
INSULATION MATERIAL	
TYPE (IEC 85)	B
EFFICIENCY	90 %
RELATIVE SHORT-CIRCUIT	
VOLTAGE	6.3 %
SUITABLE FOR	Branch circuits, (UL/CSA)
INSULATION CLASS	B
PRIMARY TAPPING	± 5 %
PRIMARY VOLTAGE 6 -	0 V
MIN	
PRIMARY VOLTAGE 7 -	0 V
MAX	
PRIMARY VOLTAGE 7 -	0 V
MIN	
PRIMARY VOLTAGE 8 -	0 V
MAX	
PRIMARY VOLTAGE 8 -	0 V
MIN	
PRIMARY VOLTAGE 9 -	0 V
MAX	
PRIMARY VOLTAGE 9 -	0 V
MIN	
RATED FREQUENCY -	
MAX	60 Hz

RATED FREQUENCY - MIN	50 Hz
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
RATED POWER	0.25 VA
SECONDARY VOLTAGE 1 - MAX	250 V
SECONDARY VOLTAGE 1 - MIN	12 V
SECONDARY VOLTAGE 10 - MAX	0 V
SECONDARY VOLTAGE 10 - MIN	0 V
SECONDARY VOLTAGE 2 - MAX	0 V
SECONDARY VOLTAGE 2 - MIN	0 V
SECONDARY VOLTAGE 3 - MAX	0 V
SECONDARY VOLTAGE 3 - MIN	0 V
SECONDARY VOLTAGE 4 - MAX	0 V
PRODUCT CATEGORY	Single-phase control transformers ST
SECONDARY VOLTAGE 4 - MIN	0 V
SECONDARY VOLTAGE 5 - MAX	0 V
SECONDARY VOLTAGE 5 - MIN	0 V
SECONDARY VOLTAGE 6 - MAX	0 V
SECONDARY VOLTAGE 6 - MIN	0 V
SECONDARY VOLTAGE 7 - MAX	0 V
SECONDARY VOLTAGE 7 - MIN	0 V
SECONDARY VOLTAGE 8 - MAX	0 V
SECONDARY VOLTAGE 8 - MIN	0 V
SECONDARY VOLTAGE 9 - MAX	0 V
SECONDARY VOLTAGE 9 - MIN	0 V

SHORT-CIRCUIT LOSSES	21 W
SHORT-TIME RATING	0.44 kVA
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT	30 W
PVS	
VOLTAGE RATING - MAX	600 V
POWER CONSUMPTION IN STANDBY MODE	7 W

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

