

Specifications



Photo is representative

Eaton 212321

Eaton Moeller® series T0 T0-2-4929US/I1/SVB-SW/L-SOND803

General specifications

PRODUCT NAME	Eaton rotary cam switch
CATALOG NUMBER	212321
MODEL CODE	T0-2-4929US/I1/SVB-SW/L-SOND803
EAN	4015082123215
PRODUCT LENGTH/DEPTH	107 mm
PRODUCT HEIGHT	122 mm
PRODUCT WIDTH	80 mm
PRODUCT WEIGHT	0.308 kg
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
CERTIFICATIONS	UL Listed CSA Certified
GLOBAL CATALOG	212321

Product specifications

ACTUATOR COLOR	Black
RATED PERMANENT CURRENT AT AC-21, 400 V	20 A
RATED UNINTERRUPTED CURRENT (IU)	20 A
SWITCHING POWER AT 400 V	5.5 kW
DEVICE CONSTRUCTION	Complete device in housing
RATED SHORT-TIME WITHSTAND CURRENT (ICW)	0.32 kA
ELECTRICAL	
CONNECTION TYPE OF MAIN CIRCUIT	Screw connection
ACTUATOR TYPE	Door coupling rotary drive
RATED CONDITIONAL SHORT-CIRCUIT CURRENT (IQ)	6 kA
DEGREE OF PROTECTION (FRONT SIDE)	IP65
DEGREE OF PROTECTION	NEMA 12
NUMBER OF SWITCHES	1
RATED OPERATING VOLTAGE (UE) - MAX	690 V
RATED OPERATING VOLTAGE (UE) - MIN	690 V
RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX	690 V
RATED OPERATIONAL POWER AT AC-23A, 400 V, 50 Hz	5.5 kW
RATED OPERATIONAL POWER AT AC-3, 380/400 V, 50 Hz	5.5 kW

Resources

DECLARATIONS OF CONFORMITY	DA-DC-00004927.pdf DA-DC-00004895.pdf
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - 212321
WARRANTY GUIDES	Selling Policy 25-000 - Distribution and Control Products and Services

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

