

Specifications

Eaton 216486

Eaton Moeller® series M22 Carrier, +label, I
0 II

General specifications

PRODUCT NAME	Eaton Moeller® series M22 Accessory Legend holder
CATALOG NUMBER	216486
MODEL CODE	M22S-ST-X93
EAN	4015082164867
PRODUCT LENGTH/DEPTH	4 mm
PRODUCT HEIGHT	50 mm
PRODUCT WIDTH	30 mm
PRODUCT WEIGHT	0.002 kg
CERTIFICATIONS	UL/CSA certification not required
CATALOG NOTES	Complete
GLOBAL CATALOG	216486

Product specifications

10.10 TEMPERATURE RISE	Not applicable.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Please enquire
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.

Resources

CATALOGS

[eaton-rmq-titan-brochure-br047004en-en-us.pdf](#)

[Flip catalog - Product Range Catalog - Command and indication](#)

[eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf](#)

DECLARATIONS OF CONFORMITY

[DA-DC-00004157.pdf](#)

[DA-DC-00004135.pdf](#)

[eaton-operating-mounting-m22-legend-holder-dimensions-003.eps](#)

[eaton-operating-mounting-m22-legend-holder-dimensions-002.eps](#)

DRAWINGS

[eaton-operating-label-m22-legend-holder-dimensions.eps](#)

[eaton-operating-actuation-m22-legend-holder-dimensions.eps](#)

[eaton-operating-mounting-m22-legend-holder-dimensions.eps](#)

ECAD MODEL

[ETN.216486.edz](#)

FLYERS

[eaton-rmq-titan-selection-aid-brochure-fl047002-en-us.pdf](#)

INSTALLATION INSTRUCTIONS

[IL04716002Z](#)

INSTALLATION VIDEOS

[RMQ Flat Design](#)

MCAD MODEL

[DA-CS-tastenzusatzschild](#)

[DA-CD-tastenzusatzschild](#)

[MCI MultiColor Light Indicator RMQ compact solution](#)

MULTIMEDIA

[easyE4 SmartWire-DT module with Remote Touch Display and RMQ multi color indicator](#)

10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
CONNECTION TO SMARTWIRE-DT	No
COLOR	Black
SHAPE	Rectangular
DESIGN	Round
DEGREE OF PROTECTION	IP66
INSCRIPTION	I O II
AMBIENT OPERATING TEMPERATURE - MAX	70 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W
OPENING DIAMETER	22 mm
OPENING HEIGHT	0 mm
RAL-NUMBER	9005
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W
WIDTH OPENING	0 mm
PRODUCT CATEGORY	Accessories

	MCI Multicolor Light Indicator M22 with SmartWire-DT
	RMQ small E-Stop emergency-stop button
PEP ECO-PASSPORT	EATO-00050-V01.01-EN
	eaton-rmq-small-e-stop-flyer-fl047006en-en-us.pdf
	eaton-rmq-flat-enclosure-flyer-fl047003en-en-us.pdf
SALES NOTES	eaton-rmq-mci-multi-color-light-indicator-flyer-fl047005en-en-us.pdf
	eaton-control circuit-devices rmq-titan-fl144090en-en-us.pdf
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - 216486

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

