Specifications

Eaton 218304

Eaton Moeller® series M22 Button lens, flat blue, R

General specification	าร
PRODUCT NAME	Eaton Moeller® series M22 Accessory Button lens
CATALOG NUMBER	218304
MODEL CODE	M22-XDL-B-X6
EAN	4015082183042
PRODUCT LENGTH/DEPTH	24 mm
PRODUCT HEIGHT	3 mm
PRODUCT WIDTH	24 mm
PRODUCT WEIGHT	0.002 kg
CERTIFICATIONS	CSA Certified UL Listed
GLOBAL CATALOG	218304



Product specification	S
ТҮРЕ	Button lenses
10.10 TEMPERATURE RISE	Not applicable.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Please enquire
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC	Does not apply, since the entire switchgear needs to

Resources	
CATALOGS	eaton-rmq-titan-brochure- br047004en-en-us.pdf
	eaton-pushbuttons-signal- towers-sensors- assortment-overview- catalog-ca047003en-en- us.pdf
	Flip catalog - Product Range Catalog - Command and indication
DECLARATIONS OF	DA-DC-00004157.pdf
	DA-DC-00004135.pdf
DRAWINGS	1160SPC-90
ECAD MODEL	ETN.218304.edz
FLYERS	eaton-rmq-titan-selection- aid-brochure-fl047002-en- us.pdf
INSTALLATION INSTRUCTIONS	<u>IL04716002Z</u>
INSTALLATION VIDEOS	RMQ Flat Design
	DA-CD-
MCAD MODEL	<u>tastenplattenlinse_flach</u>
MCAD MODEL	DA-CS-
MCAD MODEL	
MCAD MODEL	DA-CS-
MCAD MODEL MULTIMEDIA	DA-CS- tastenplattenlinse flach easyE4 SmartWire-DT module with Remote Touch Display and RMQ
	DA-CS- tastenplattenlinse flach easyE4 SmartWire-DT module with Remote Touch Display and RMQ multi color indicator MCI MultiColor Light Indicator RMQ compact
	DA-CS- tastenplattenlinse flach easyE4 SmartWire-DT module with Remote Touch Display and RMQ multi color indicator MCI MultiColor Light Indicator RMQ compact solution MCI Multicolor Light Indicator M22 with
	DA-CS- tastenplattenlinse flach easyE4 SmartWire-DT module with Remote Touch Display and RMQ multi color indicator MCI MultiColor Light Indicator RMQ compact solution MCI Multicolor Light Indicator M22 with SmartWire-DT RMQ small E-Stop
	DA-CS- tastenplattenlinse flach easyE4 SmartWire-DT module with Remote Touch Display and RMQ multi color indicator MCI MultiColor Light Indicator RMQ compact solution MCI Multicolor Light Indicator M22 with SmartWire-DT RMQ small E-Stop emergency-stop button eaton-rmq-mci-multi- color-light-indicator-flyer-

SHOCK	be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	ls the panel builder's responsibility.
10.9.2 POWER- FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	ls the panel builder's responsibility.
AMBIENT OPERATING TEMPERATURE - MAX	70 °C
BUILT-IN DIAMETER	22.5 mm
EQUIPMENT HEAT DISSIPATION, CURRENT- DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT- DEPENDENT PVID	0 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
DIAMETER	22.2 mm
LENS COLOR	Blue
DESIGN	Flat
INSCRIPTION	Individual inscription possible: ≤ 5 characters: letter height 5 mm Individual inscription possible: > 5 characters: letter height 3 mm
·	

Round

LENS SHAPE

	eaton-control circuit- devices rmq-titan- fl144090en-en-us.pdf
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - 218304

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	



Eaton Corporation plc

Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.









