

Specifications



Eaton CCP2-2-30CC

Eaton Bussmann series CCP UL98 fusible disconnect, 600 Vac, 125 Vdc, 30A, UL98 fusible disconnect, Two-pole, 60 Hz, Class CC, 200 - CCP2-2-30CC

General specifications

PRODUCT NAME	Eaton Bussmann series CCP UL98 fusible disconnect
CATALOG NUMBER	CCP2-2-30CC
UPC	051712709170
PRODUCT LENGTH/DEPTH	3.9 in
PRODUCT HEIGHT	3.1 in
PRODUCT WIDTH	1.4 in
PRODUCT WEIGHT	1.46 lb
WARRANTY	Not Applicable
COMPLIANCES	RoHS Compliant
CERTIFICATIONS	UL 98

Electrical rating

AMPERAGE RATING	30A
FREQUENCY RATING	50/60 Hz
SHORT-CIRCUIT RATING	200 kA
VOLTAGE RATING	600 Vac, 125 Vdc

General information

SPECIAL FEATURES	Finger Safe, 1/4" LOTO
SUITABLE FOR FUSES	LP-CC-1/2 to LP-CC-30 KTK-R-1/10 to KTK-R-30 FNQ-R-1/4 to FNQ-R-30

Physical details

FUSE TYPE	Class CC
NUMBER OF POLES	Two-pole

Resources

CATALOGS	Bussmann series complete full line catalog no. 1007 CCP2-2-30CC~2 Pole Comp Ckt Protect 30A
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - CCP2-2-30CC

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

