Specifications



Eaton CCP2R-3-30CF

Eaton Bussmann series CCP UL98 fusible disconnect, Finger Safe, Lock-On provision, 600 Vac, 125 Vdc, 225A, UL98 fusible disconnect, Three-pole, 200 kA - CCP2R-3-30CF

General specifications		
PRODUCT NAME	Eaton Bussmann series CCP UL98 fusible disconnect	
CATALOG NUMBER	CCP2R-3-30CF	
UPC	051712709859	
PRODUCT LENGTH/DEPTH	2.9 in	
PRODUCT HEIGHT	3.7 in	
PRODUCT WIDTH	0.3 in	
PRODUCT WEIGHT	3.7 lb	
WARRANTY	Not Applicable	
COMPLIANCES	CCC Marked	
CERTIFICATIONS	Contact Manufacturer	



Electrical rating	
AMPERAGE RATING	225 A
SHORT-CIRCUIT RATING	200 kAIC
VOLTAGE RATING	600 Vac, 125 Vdc

Three-pole

General information	
SPECIAL FEATURES	Finger Safe, Lock-On provision
SUITABLE FOR FUSES	TCF6 to TCF30 TCF1RN to TCF30RN FCF1RN to FCF30RN

Resources	
CATALOGS	CCP2R-3-30CF~CCP2 3P 30A CF W/ROTARY HandM RIGHT
	Bussmann series complete full line catalog no. 1007
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - CCP2R-3-30CF

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc

Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

 $\hbox{@ 2025 Eaton.}$ All Rights Reserved.

Follow us on social media to get the latest product and support information.









