Specifications







Eaton CCP2RL-3-30CF

Eaton Bussmann series CCP UL98 fusible disconnect, Finger Safe, Lock-On provision, 600 Vac, 125 Vdc, 225A, UL98 fusible disconnect, Three-pole, 200 kA - CCP2RL-3-30CF

General specification	ns
PRODUCT NAME	Eaton Bussmann series CCP UL98 fusible disconnect
CATALOG NUMBER	CCP2RL-3-30CF
UPC	051712709873
PRODUCT LENGTH/DEPTH	2.9 in
PRODUCT HEIGHT	3.7 in
PRODUCT WIDTH	0.3 in
PRODUCT WEIGHT	3.7 lb
WARRANTY	Not Applicable
COMPLIANCES	CCC Marked
CERTIFICATIONS	Contact Manufacturer



Electrical rating	
AMPERAGE RATING	225 A
SHORT-CIRCUIT RATING	200 kAIC
VOLTAGE RATING	600 Vac, 125 Vdc

Physical details		
NUMBER OF POLES	Three-pole	

General information	
SPECIAL FEATURES	Finger Safe, Lock-On provision
SUITABLE FOR FUSES	TCF6 to TCF30 TCF1RN to TCF30RN FCF1RN to FCF30RN

Resources	
CATALOGS	Bussmann series complete full line catalog no. 1007 CCP2RL-3-30CF~CCP2 3P
	30A CF W/ ROTARY HandM LEFT
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - CCP2RL-3-30CF

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	



Eaton Corporation plc

Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

 $\hbox{@ 2025 Eaton.}$ All Rights Reserved.

Follow us on social media to get the latest product and support information.









