Specifications

Photo is representative

Eaton DFJ-12

Eaton Bussmann series DFJ high speed fuse, 600 Vac or less, 450 Vdc or less, 102A, 200 kAIC at 600 Vac, 100 kAIC 450 Vdc, Non Indicating, High speed fuse, Ferrule end X ferrule end, Class J, Melamine tube

S
Eaton Bussmann series DFJ high speed fuse
DFJ-12
051712653275
3 in
0.5 in
1 in
0.231 lb
Not Applicable
CE Marked RoHS Compliant
UL Listed CSA Certified



Electrical rating	
AMPERAGE RATING	102A
INTERRUPT RATING	100 kAIC 450 Vdc 200 kAIC at 600 Vac
VOLTAGE RATING	600 Vac or less, 450 Vdc or less

Physical details	
MATERIAL	Melamine tube
PACKAGING TYPE	Standard

General information	
CLASS	Class J
CONNECTION	Ferrule end x ferrule end
FUSE INDICATOR	Non Indicating

Resources	
CATALOGS	Bussmann series complete full line catalog no. 1007
CERTIFICATION REPORTS	Eaton Bussmann EU Declaration of conformity 93-68-EEC200A
SPECIFICATIONS AND DATASHEETS	<u>Eaton Specification Sheet -</u> <u>DFJ-12</u>
TECHNICAL DATA SHEETS	DFJ-12~DRIVE FUSE
TECHNICAL SERVICE BULLETINS	Datasheet - FNQ-30

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	



Eaton Corporation plc

Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.









