

Specifications

Eaton FWH-025A6F

Eaton Bussmann series FWH high speed fuse, DC common bus, 25A RMS (200% minimum opening current at rated voltage), 50 kAIC at 0.25-20A, 20 kAIC at 25-30A, Ferrule end X ferrule end, Standard

General specifications

PRODUCT NAME	Eaton Bussmann series FWH high speed fuse
CATALOG NUMBER	FWH-025A6F
UPC	051712796514
EAN	5027590061193
PRODUCT LENGTH/DEPTH	1.25 in
PRODUCT HEIGHT	0.25 in
PRODUCT WIDTH	0.25 in
PRODUCT WEIGHT	0.4 lb
WARRANTY	Not Applicable
COMPLIANCES	CE Marked RoHS Compliant
CERTIFICATIONS	UL Recognized CSA Certified

Electrical rating

AMPERAGE RATING	25A RMS (200% minimum opening current at rated voltage)
INTERRUPT RATING	50 kAIC at 0.25-20A 20 kAIC at 25-30A
VOLTAGE RATING	500 Vac/dc (35-800 A only)

General information

CONNECTION	Ferrule end x ferrule end
FUSE INDICATOR	Non Indicating

Physical details

PACKAGING TYPE	Standard
-----------------------	----------

Resources

CATALOGS	Bussmann series complete full line catalog no. 1007
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - FWH-025A6F FWH-025A6F~BUSS SEMICONDUCTOR, 500V
TECHNICAL DATA SHEETS	Bussmann series FWH 6x32mm high speed fuse data sheet no. 720038
TECHNICAL SERVICE BULLETINS	Datasheet - FNQ-30

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

