Specifications







Eaton KLM-2

Eaton Bussmann series KLM fuse, 2 A, Non-indicating, Ferrule end x ferrule end, 50 kAIC at 600 Vdc, 100 kAIC at 600 V, Melamine tube, Nickel-plated bronze endcap, 600 V, 600 Vdc

General specifications		
PRODUCT NAME	Eaton Bussmann series KLM fuse	
CATALOG NUMBER	KLM-2	
UPC	051712695091	
PRODUCT LENGTH/DEPTH	0.001 in	
PRODUCT HEIGHT	0.001 in	
PRODUCT WIDTH	0.001 in	
PRODUCT WEIGHT	0.18 lb	
WARRANTY	Not Applicable	
COMPLIANCES	RoHS Compliant CE Marked	



Electrical rating	
AMPERAGE RATING	2 A
INTERRUPT RATING	50 kAIC at 600 Vdc 100 kAIC at 600 Vac
VOLTAGE RATING	600 Vac, 600 Vdc

Physical details	
MATERIAL	Nickel-plated bronze endcap Melamine tube
PACKAGING TYPE	Standard

General information	
CONNECTION	Ferrule end x ferrule end
FUSE INDICATOR	Non-indicating
SPECIAL FEATURES	Indicating

Resources	
CATALOGS	Bussmann series complete full line catalog no. 1007
MULTIMEDIA	Bussmann series Fuseology
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - KLM-2
TECHNICAL DATA SHEETS	KLM-2~LIMITRON FAST ACTING FUSE
TECHNICAL SERVICE BULLETINS	Datasheet - FNQ-30

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	



Eaton Corporation plc

Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com



information.



latest product and support

Follow us on social media to get the



