

Specifications



Eaton KLM-30

Eaton Bussmann series KLM fuse, 30 A, Non-indicating, Ferrule end x ferrule end, 100 kAIC at 600 V, 50 kAIC at 600 Vdc, Melamine tube, Nickel-plated bronze endcap, 600 V, 600 Vdc

General specifications

PRODUCT NAME	Eaton Bussmann series KLM fuse
CATALOG NUMBER	KLM-30
UPC	051712695305
PRODUCT LENGTH/DEPTH	0.001 in
PRODUCT HEIGHT	0.001 in
PRODUCT WIDTH	0.001 in
PRODUCT WEIGHT	0.18 lb
WARRANTY	Not Applicable
COMPLIANCES	CE Marked RoHS Compliant

Electrical rating

AMPERAGE RATING	30 A
INTERRUPT RATING	100 kAIC at 600 Vac 50 kAIC at 600 Vdc
VOLTAGE RATING	600 Vac, 600 Vdc

General information

CONNECTION	Ferrule end x ferrule end
FUSE INDICATOR	Non-indicating
SPECIAL FEATURES	Non-indicating

Physical details

MATERIAL	Nickel-plated bronze endcap Melamine tube
PACKAGING TYPE	Standard

Resources

CATALOGS	Bussmann series complete full line catalog no. 1007
MULTIMEDIA	Bussmann series Fuseology
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - KLM-30
TECHNICAL DATA SHEETS	KLM-30~LIMITRON FAST ACTING FUSE
TECHNICAL SERVICE BULLETINS	Datasheet - FNO-30

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

