

Specifications



Photo is representative



Eaton OPM-NG-SC3

Eaton Bussmann series Optima fuse holders, 0-30 A, Three-pole, 65°C, -10°C, 200 kA, Philslot screws/pressure plate, 200 kAIC, Thermoplastic, 35 mm DIN rail, #8 Screw, 600 V or less, Use with LP-CC, KTK-R, FNQ-R Class CC

General specifications

PRODUCT NAME	Eaton Bussmann series Optima fuse holders
CATALOG NUMBER	OPM-NG-SC3
UPC	051712674171
PRODUCT LENGTH/DEPTH	2.7 in
PRODUCT HEIGHT	3.5 in
PRODUCT WIDTH	1.8 in
PRODUCT WEIGHT	0.423 lb
WARRANTY	Not Applicable
COMPLIANCES	CE Marked RoHS Compliant
CERTIFICATIONS	Contact Manufacturer UL Listed CSA Certified

Electrical rating

AMPERAGE RATING	0-30A
INTERRUPT RATING	200 kAIC
SHORT-CIRCUIT RATING	200 kA
VOLTAGE RATING	600 V or less

General information

CONNECTION	Phislot screws/pressure plate
MOUNTING METHOD	35 mm DIN rail #8 Screw
USED WITH	For use with LP-CC, KTK-R, FNQ-R Class CC Rejection fuse

Physical details

MATERIAL	Thermoplastic
NUMBER OF POLES	Three-pole
OPERATING TEMPERATURE - MAX	65 °C
OPERATING TEMPERATURE - MIN	-10 °C

Resources

CATALOGS	Bussmann series full line catalog 1007, section 8 fuse blocks and holders Bussmann series complete full line catalog no. 1007
MULTIMEDIA	Bussmann series Fuseology
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - OPM-NG-SC3
TECHNICAL DATA SHEETS	Bussmann series OPM-NG 3-pole overcurrent protection module no. 1109
TECHNICAL SERVICE BULLETINS	Datasheet - FNQ-30

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

