

Specifications

Photo is representative

Eaton SC-3

Eaton Bussmann Series Class G fuse, SC, fast-acting, current limiting fuse, 3 A, rejection style fuse, interrupting rating of 100 kA at 600 Vac and 10 kA at 170 Vdc

General specifications

PRODUCT NAME	Eaton Bussmann series SC fuse
CATALOG NUMBER	SC-3
UPC	051712250030
PRODUCT LENGTH/DEPTH	1.31 in
PRODUCT HEIGHT	0.41 in
PRODUCT WIDTH	0.41 in
PRODUCT WEIGHT	0.163 lb
WARRANTY	Not Applicable
COMPLIANCES	RoHS Compliant



Powering Business Worldwide

Electrical rating

AMPERAGE RATING	3 A
INTERRUPT RATING	10 kAIC at 170 Vdc 100 kAIC at 600 Vac
VOLTAGE RATING	600 Vac, 170 Vdc

General information

CLASS	Class G
CONNECTION	Ferrule end x ferrule end
FUSE INDICATOR	Non-indicating
SPECIAL FEATURES	Ferrule design, Type P

Physical details

PACKAGING TYPE	Standard
-----------------------	----------

Resources

CATALOGS	Low Voltage Branch Circuit Fuse Chapter Bussmann Full Line Catalog
COMPLIANCE INFORMATION	RoHS Search Tool
MULTIMEDIA	Bussmann series Fuseology
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - SC-3
TECHNICAL DATA SHEETS	Bussmann series Rejecting Fuses data sheet no. 1024

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

