

Specifications

Eaton T30030-2CR

Eaton Bussmann series Class T modular fuse block, CR, 300 Vac/Vdc or less individual control circuits, 0-30 A, Two-pole, Class T, Box lug, 200 kAIC, Glass polyester, #2 AWG Cu/Al

General specifications

PRODUCT NAME	Eaton Bussmann series Class T modular fuse block
CATALOG NUMBER	T30030-2CR
UPC	051712147903
PRODUCT LENGTH/DEPTH	2.5 in
PRODUCT HEIGHT	0.5 in
PRODUCT WIDTH	3 in
PRODUCT WEIGHT	0.32 lb
WARRANTY	Not Applicable
COMPLIANCES	RoHS Compliant
CERTIFICATIONS	Contact Manufacturer UL Recognized CSA Certified

Electrical rating

AMPERAGE RATING	0-30A
INTERRUPT RATING	200 kAIC
SHORT-CIRCUIT RATING	200 kA
VOLTAGE RATING	300 Vac/dc

General information

CLASS	Class T
CONNECTION	Box lug
SPECIAL FEATURES	CR

Physical details

MATERIAL	Glass polyester
NUMBER OF POLES	Two-pole
WIRE SIZE	#2 AWG Cu/Al

Resources

CERTIFICATION REPORTS	Eaton Bussmann EU Declaration of conformity 93-68-EEC2203
MULTIMEDIA	Bussmann series Fuseology
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - T30030-2CR

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

