Specifications



Photo is representative





Eaton SC-2

Eaton Bussmann Series Class G fuse, SC, fast-acting, current limiting fuse, 2 A, rejection style fuse, interrupting rating of 100 kA at 600 Vac and 10 kA at 170 Vdc

General specifications	
PRODUCT NAME	Eaton Bussmann series SC fuse
CATALOG NUMBER	SC-2
UPC	051712250023
PRODUCT LENGTH/DEPTH	1.31 in
PRODUCT HEIGHT	0.41 in
PRODUCT WIDTH	0.41 in
PRODUCT WEIGHT	0.1 lb
WARRANTY	Not Applicable
COMPLIANCES	RoHS Compliant CE Marked
PRODUCT TYPE	Fuse

Electrical rating

AMPERAGE RATING	2 A
INTERRUPT RATING	100 kAIC at 600 Vac 10 kAIC at 170 Vdc
VOLTAGE RATING	600 Vac, 170 Vdc

Physical details

PACKAGING TYPE	Standard

General information

CLASS	Class G
CONNECTION	Ferrule end x ferrule end
FUSE INDICATOR	Non-indicating
SPECIAL FEATURES	Ferrule design, Type P

Resources

CATALOGS	Low Voltage Branch Circuit Fuse Chapter Bussmann Full Line Catalog
COMPLIANCE INFORMATION	RoHS Search Tool
MULTIMEDIA	Bussmann series Fuseology
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - SC-2
TECHNICAL DATA SHEETS	Bussmann series KRP-CL Class L fuse data sheet no.1016 Bussmann series Rejecting Fuses data sheet no. 1024
TECHNICAL SERVICE BULLETINS	Datasheet - FNQ-30

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.