

- Operated by lifting the foot tip
- Silent operation
- Protection against opening
- Version with LED memory


Series 485

Housing material	Sheet steel, epoxy grey painting
Front material	Sheet steel, epoxy white painting
Operation	NC reed contact
Type of connection	Terminals
Operating temperature	-15°C to +55°C
Protection rating	IP 40
Standard equipment	Set with 2 reset keys (excluding 485-ME)

485-ME



Dimensions



Series 485

Foot-operated panic button

Foot-operated button silently actuated by slightly raising the foot. The internal reed contact is designed for NC operation. The mechanically high-resistance steel case is self-protected against opening.

Version 485-I is equipped with self-retaining pedal.

To reset, a specific key included in the package is necessary (keys are different for each product). 4-terminal connection: 2 for contact and 2 for anti-tampering.

Version 485-ME: LED memory with control centre reset (by cutting power supply). 6-terminal connection: 2 for contact, 2 for anti-tampering, 2 for 12 V DC power supply.

Order codes

Code	Connection type	Max voltage	Max current	Max power	Power supply	LED memory	Connections	Package weight	Notes
485-I	NC	75 V DC	1 A	10 W	-	no	4 terminals	1.92 Kg	key reset
485-ME	NC	75 V DC	1 A	10 W	12 V DC - 10 mA	yes	6 terminals	1.75 Kg	control centre reset

Accessories

CSA06632	Spare key for 485-I