

Product Environmental Profile





P1 Switch Disconnector with I2H Enclosure, Auxiliary Block & Screening Plate

Representative product	P1-40/I2H/MBS/SVB-SW/HI11 (Y7-199920) PSR Product Category: Disconnectors
Description of the product	Eaton's Switch Disconnector are designed to turn off all or part of an electrical installation by disconnecting the installation or part of the installation of all electrical energy, for safety reasons. These switch disconnectors have total 3 poles with I2H enclosure, surface mountable with Auxiliary block and screening plate and with STOP function.
Homogeneous Environmental Families Covered	The PEP concerns following product offerings from Eaton Moeller® series P1 Main switch disconnector, as mentioned below: P1-40/I2H/MBS/SVB-SW/HI11 (Y7-199920) (Reference), P1-25/I2H/MBS/SVB-SW/HI11 (Y7-182416), P1-32/I2H/MBS/SVB-SW/HI11 (Y7-182420), P1-25/I2H/MBS/SVB/HI11 (Y7-182415), P1-32/I2H/MBS/SVB/HI11 (Y7-182419), P1-40/I2H/MBS/SVB/HI11 (Y7-199918) *[The product market is spread globally. Different scenarios are studied considering distribution in UK and outside Europe and separate extrapolation factors are given in this PEP considering Europe market as reference]
Functional unit	"Turn off all or part of an installation by separating the installation or part of the installation of all electrical energy or earth, for safety reasons with a rated voltage 690V, and rated current 40A, ensuring isolation characterised by a rated voltage 6000 V AC, and with IP Rating of IP65, according to the appropriate use scenario, and during the reference service life of the product of 20 years."

Company information

Eaton Production International GmbH, Claylands Avenue, Dukeries Industrial Estate,

Worksop, United Kingdom, S81 7DJ

Email: <u>productstewardship-es@eaton.com</u>

Constituent Materials			
Reference product mass	7.91E-01 kg (With packaging)		
Category PEP Material	Materials	Mass (kg)	Percentage (%)
Plastic	Polycarbonate (PC)	2.61E-01	33.0%
Metal	Steel	1.89E-01	23.9%
Plastic	Polyamide (PA)	1.54E-01	19.5%
Others	Cardboard	8.46E-02	10.7%
Metal	Stainless Steel	6.36E-02	8.0%
Metal	Brass	2.98E-02	3.8%
Plastic	Polybutylene terephthalate (PBT)	3.70E-03	0.5%
Metal	Silver	2.11E-03	0.3%
Others	Labels	1.40E-03	0.2%
Plastic	Ethylene Vinyl Acetate (EVA)	8.00E-04	0.1%
Plastic	Silicon Rubber	4.67E-04	0.1%
Plastic	Polyethylene Film	4.53E-04	0.1%
	Total	7.91E-01	100.0%

Substance Assessment

The representative product is compliant with the EU-RoHS Directive (2011/65/EU) without exemption and the product doesn't contain any Substance-of-Very-High-Concern (SVHC) on the Candidate List of the EU-REACH Regulation (1907/2006/EC).

Additional Envir	onmental Information
Manufacturing	The reference product is assembled at an Eaton plant in United Kingdom, holding management
Manufacturing	system certifications according to ISO 14001 standards.
Distribution	Eaton is committed to minimizing weight and volume of product and packaging with focus to optimize
Distribution	transport efficiency.
Installation	The installation process does not require any energy consumption and there is no waste other than
Ilistaliation	the obsolete product packaging generated during this step.
Use	The product requires energy consumption during operation.
	The recyclability rate of the overall product is 91.79% if it is properly dismantled prior to shredding. The
End of life	rate is calculated based on "ECO'DEEE recyclability and recoverability calculation method" (version V1,
	20 Sep. 2008 presented to the French Agency for Environment and Energy Management: ADEME).

_			
	ironmeı	atai in	1 M A CTC
		псани	IDacts

The calculation of the environmental impacts is the result of the Product's Life Cycle Analysis in accordance with ISO 14040/44, covering the entire lifecycle, i.e., "Cradle-to-Grave" including the following life cycle phases: production, distribution, installation, use and end of life. System modelling was carried out using the commercial LCA software EIME v6.2 with database version CODDE-2024-04.

Indicators Set: PEF EF 3.1 (Compliance: PEP ed.4, EN15804+A2) v2.0

	- (p , , , , , , , , , , , , , , , , ,
Manufacturing Phase	The product is assembled as well as packed at Eaton Production International GmbH, United Kingdom, plant. Energy model used: United Kingdom
Distribution Phase	Distribution of the product in its packaging from Eaton's last logistics platform to the installation place is considered in Europe.
Installation Phase	Product is installed in Europe. Treatment of packaging waste is considered in this phase as per country specific statistics given in PSR. Energy model used: Europe
Use Phase	Reference lifetime: 20 Years Usage profile: The product has power loss of 10.5 W at full load condition. For industrial and commercial applications under low voltage scenario considering 50% of the loading rate and 30% use time rate, total losses are 137.97 kWh over the 20 years. Product do not require any maintenance/replacement during useful life. Energy Model Used: Europe
End of life Phase	Product is disposed with WEEE guidelines. Energy model used: Europe
Module-D	Module D is calculated according to PCR-ed4-EN-2021 09 06 based on the materials recycled and the modelled end-of-life scenario. It expresses the net benefits and loads beyond the boundaries of the system and are not to be included in the life cycle totals.

Environmental Impact Indicators: Mandatory

Mandatory environmental impact indicators	Units	Sum	Manufacturing	Distribution	Installation	Use (Only B6)	End of life
Depletion of abiotic resources – elements (ADP-e)	kg eq. Sb	3.06E-03	3.04E-03	7.43E-09	3.88E-09	1.36E-05	5.39E-06
Depletion of abiotic resources - fossil fuels (ADP-f)	МЈ	1.12E+03	1.43E+02	2.63E+00	8.99E-01	9.15E+02	5.60E+01
Acidification (AP)	mole of H+ equiv	2.02E-01	2.79E-02	1.19E-03	2.81E-04	1.68E-01	4.47E-03
Freshwater eutrophication (EP-fw)	kg P eq.	4.30E-04	1.53E-04	7.08E-08	1.27E-06	1.01E-04	1.74E-04
Marine aquatic eutrophication (EP-m)	kg of N equiv	2.74E-02	4.87E-03	5.60E-04	1.34E-04	2.11E-02	7.53E-04
Terrestrial eutrophication (EP-t)	mole of N equiv	6.35E-01	4.65E-02	6.14E-03	9.18E-04	5.73E-01	8.67E-03
Climate change – total (GWP)	kg CO2 eq.	4.12E+01	5.35E+00	1.88E-01	2.42E-01	3.44E+01	1.01E+00

Mandatory environmental impact indicators	Units	Sum	Manufacturing	Distribution	Installation	Use (Only B6)	End of life	Module D
Climate change – biogenics (GWP-b)	kg CO2 eq.	1.96E-01	-5.45E-02	0.00E+00	1.38E-01	1.06E-01	5.75E-03	5.66E-02
Climate change - fossil fuels (GWP-f)	kg CO2 eq.	4.10E+01	5.41E+00	1.88E-01	1.04E-01	3.43E+01	1.01E+00	-3.03E+00
Climate change - land use and land use transformation (GWP-lu)	kg CO2 eq.	3.88E-04	3.88E-04	0.00E+00	0.00E+00	0.00E+00	1.55E-07	-3.31E-04
Ozone depletion (ODP)	kg equivalent CFC-11	4.90E-07	2.85E-07	2.89E-10	1.34E-09	1.93E-07	1.02E-08	-1.58E-07
Photochemical ozone formation (POCP)	kg of NMVOC equiv	7.61E-02	1.36E-02	1.55E-03	2.06E-04	5.81E-02	2.65E-03	-6.29E-03
Water scarcity (WP)	m3 of equiv. deprivation worldwide	4.74E+00	1.93E+00	7.16E-04	7.64E-03	2.44E+00	3.64E-01	-1.21E+00

Inventory Flow Indicators: Mandatory

-								
Inventory flow indicators	Units	Sum	Manufacturing	Distribution	Installation	Use (Only B6)	End of life	Module D
Use of renewable primary energy, excluding renewable primary energy resources used as raw materials	MJ	4.02E+02	6.71E+00	3.51E-03	1.40E-01	3.95E+02	9.00E-01	-1.33E+00
Use of renewable primary energy resources used as raw materials	MJ	2.42E+00	2.42E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	-1.25E+00
Total use of renewable primary energy resources (primary energy and primary energy resources used as raw materials)	MJ	4.05E+02	9.13E+00	3.51E-03	1.40E-01	3.95E+02	9.00E-01	-2.58E+00
Use of non-renewable primary energy, excluding non-renewable primary energy resources used as raw materials	MJ	1.10E+03	1.30E+02	2.63E+00	8.99E-01	9.15E+02	5.60E+01	-5.69E+01
Use of non-renewable primary energy resources used as raw materials	MJ	1.33E+01	1.33E+01	0.00E+00	0.00E+00	0.00E+00	0.00E+00	-1.08E+01
Total use of non-renewable primary energy resources (primary energy and primary energy resources used as raw materials)	MJ	1.12E+03	1.43E+02	2.63E+00	8.99E-01	9.15E+02	5.60E+01	-6.77E+01
Use of secondary materials	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Use of renewable secondary fuels	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Use of non-renewable secondary fuels	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00

Inventory flow indicators	Units	Sum	Manufacturing	Distribution	Installation	Use (Only B6)	End of life
Net use of fresh water	m3	1.13E-01	4.52E-02	1.67E-05	6.10E-04	5.85E-02	8.48E-03
Components for re-use	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Materials for recycling	kg	9.93E-01	2.67E-01	0.00E+00	6.96E-02	0.00E+00	6.56E-01
Materials for energy recovery	kg	1.23E-02	5.22E-05	0.00E+00	7.78E-03	0.00E+00	4.50E-03
Exported energy	MJ by energy vector	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Hazardous waste disposed of	kg	1.99E+01	1.60E+01	0.00E+00	5.46E-03	3.18E+00	7.13E-01
Non-hazardous waste disposed of	kg	6.63E+00	1.83E+00	6.62E-03	3.38E-02	4.61E+00	1.45E-01
Radioactive waste disposed of	kg	2.79E-03	6.57E-04	4.72E-06	6.10E-06	2.07E-03	4.69E-05
Biogenic carbon content of the product	kg of C.	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Biogenic carbon content of the associated packaging	kg of C.	5.80E-02	5.80E-02	0.00E+00	0.00E+00	0.00E+00	0.00E+00

Module D	
-2.81E-02	
0.00E+00	
0.00E+00	
0.00E+00	
0.00E+00	
-8.45E+00	1
-8.65E-01	
-4.59E-04	
0.00E+00	
0.00E+00	

Environmental Impact Indicators: Optional

Optional Environmental impact indicators	Units	Sum	Manufacturing	Distribution	Installation	Use (Only B6)	End of life
Ecotoxicity, freshwater	CTUe	1.28E+02	2.96E+01	1.24E-01	1.40E+00	9.49E+01	1.87E+00
Human toxicity, cancer	CTUh-C	1.47E-06	1.46E-06	3.31E-12	1.02E-08	4.46E-09	3.78E-10
Human toxicity, non-cancer	CTUh-nC	3.10E-07	2.31E-07	6.41E-11	2.89E-10	5.96E-08	1.88E-08
Ionising radiation, human health	kBq U ²³⁵ eq.	6.77E+01	1.20E+01	4.59E-04	1.08E-02	5.55E+01	2.74E-01
Land use	No dimension	3.59E+00	1.38E+00	0.00E+00	3.53E-04	1.84E+00	3.71E-01
EF-particulate Matter	Disease occurrence	1.84E-06	2.81E-07	9.72E-09	1.66E-09	1.52E-06	2.78E-08
Total Primary Energy	MJ	1.52E+03	1.52E+02	2.63E+00	1.04E+00	1.31E+03	5.69E+01

Module D
-1.78E+01
-7.95E-07
-1.14E-07
-5.94E+00
-9.23E-01
-1.44E-07
-7.03E+01

To evaluate the environmental impact of other product covered by this PEP, multiply the impact figures by-

Multiplying Factors for Manufacturing, distribution, installation, End of Life and Module-D phase Phase (For EU market):

Part No.	Description	Extrapolation Factors for Manufacturing, distribution, installation, End of Life and Module-D phase
Y7-199920	P1-40/I2H/MBS/SVB-SW/HI11	1.00
(Reference)	11-40/1211/10103/300-300/11111	1.00
Y7-182416	P1-25/I2H/MBS/SVB-SW/HI11	1.00
Y7-182420	P1-32/I2H/MBS/SVB-SW/HI11	1.00
Y7-182415	P1-25/I2H/MBS/SVB/HI11	1.00
Y7-182419	P1-32/I2H/MBS/SVB/HI11	1.00
Y7-199918	P1-40/I2H/MBS/SVB/HI11	1.00

Multiplying Factors for Use Phase (For EU market):

Part No.	Description	Extrapolation Factor for Use Phase
Y7-199920 (Reference)	P1-40/I2H/MBS/SVB-SW/HI11	1.00
Y7-182416	P1-25/I2H/MBS/SVB-SW/HI11	0.31
Y7-182420	P1-32/I2H/MBS/SVB-SW/HI11	0.51
Y7-182415	P1-25/I2H/MBS/SVB/HI11	0.31
Y7-182419	P1-32/I2H/MBS/SVB/HI11	0.51
Y7-199918	P1-40/I2H/MBS/SVB/HI11	1.00

Factors for Manufacturing, Distribution, Installation, End of Life and Module-D phase for different geographical sales regions:

Product	Geographica I regions	Phases	ADP-e (kg Sb eq.)	ADP-f (MJ)	AP (mol H+ eq.)	EP-fw (kg P eq.)	EP-m (kg N eq.)	EP-t (mol N eq.)	GWP (kg CO2 eq.)	GWP-b (kg CO2 eq	GWP-f (kg CO2 eq)	GWP- lu (kg CO2 eq.)	ODP (kg CFC- 11 eq.)	POCP (kg NMV OC eq.)	WP (m3 eq.)
	Europe	All Phases	1.00												
Y7-199920	United Kingdom Y7-199920 (Reference)	Manufacturin g, Installation, EoL, Module- D	1.00												
		Distribution	0.29												
		Manufacturin g	1.00												
Outside Europe		Distribution	1.22	1.22	7.00	1.23	3.56	3.55	1.34	1.00	1.34	1.00	1.14	3.63	1.17
	Europe	Installation	0.55	0.61	0.65	0.02	0.34	0.64	0.67	0.96	0.29	1.00	0.79	0.62	0.16
	End of Life	0.01	0.13	0.60	0.01	0.91	1.02	0.38	0.55	0.38	0.00	2.98	0.74	0.09	

Factors for use phase for different geographical sales regions:

Product	Geographical regions	ADP-e (kg Sb eq.)	ADP- f (MJ)	AP (mol H+ eq.)	EP- fw (kg P eq.)	EP-m (kg N eq.)	EP-t (mol N eq.)	GWP (kg CO2 eq.)	GWP-b (kg CO2 eq.)	GWP-f (kg CO2 eq.)	GWP- lu (kg CO2 eq.)	ODP (kg CFC-11 eq.)	POCP (kg NMVOC eq.)	WDP (m3 eq.)
	Europe (Reference)								1.00					
	Germany	1.09	0.86	1.50	0.54	1.34	1.39	1.07	0.73	1.07	1.00	1.43	1.35	1.28
	UK	0.79	0.75	0.68	0.79	0.69	1.17	0.71	1.19	0.71	1.00	0.82	0.61	0.66
Y7-199920	Austria	1.65	0.23	0.44	0.01	0.40	0.63	0.37	0.65	0.37	1.00	0.37	0.36	1.10
(Reference)	Netherlands	0.79	0.77	0.80	0.18	0.95	0.98	1.14	1.33	1.14	1.00	1.01	0.94	0.92
(Kererence)	India	0.60	2.47	5.87	0.16	5.13	3.64	3.93	0.25	3.94	1.00	4.74	5.44	2.69
	Czech Republic	0.45	1.66	2.35	1.77	2.05	1.77	1.59	0.44	1.59	1.00	2.02	2.12	1.20
	Finland	0.73	0.86	0.91	1.59	0.68	1.42	0.39	0.61	0.39	1.00	0.71	0.56	0.54
	Denmark	0.83	0.35	1.16	0.04	0.98	1.66	0.56	0.90	0.56	1.00	1.30	0.86	0.58

Disclaimer

This Product Environmental Profile and its content is based on information available to us. It refers to the product at the date of issue. We make no express or implied representations or warranties with respect to the information contained herein.

		Drafting rules	1					
Registration Number	EATO-00161-V01.01-EN	PCR-ed4-EN-2021 09 06						
Verifier accreditation	VH53	Supplemented by	PSR-0005-ed3.1-EN-2023 08 12					
Number	11.00	Cappienienes sy	1 311 3033 34312 211 2323 33 12					
Date of issue	06-2024	Information and	www.pep-ecopassport.org					
Date of issue	00-2024	reference documents						
		Validity period	5 years					
Independent verification of	006							
Internal	rnal X External							
The PCR review was conduc								
(DDemain)								
PEPs are compliant with XP	PEP							
The components of the pres	PASS							
other program.	PORT							
Document complies with ISC	- Janes							
Type III environmental decla								