

Product Environmental Profile





P1 Switch Disconnector with I2 Enclosure

Representative	P1-40/I2/SVB-SW (Y7-199912)
product	PSR Product Category: Disconnectors
Description of the product	Eaton's Switch Disconnector are designed to turn off all or part of an electrical installation by disconnecting the installation or part of the installation of all electrical energy, for safety reasons. These switch disconnectors have total 3 poles with I2 Enclosure, surface mountable and with STOP Function
Homogeneous Environmental Families Covered	The PEP concerns following product offerings from Eaton Moeller® series P1 switch disconnector, as mentioned below: P1-40/I2/SVB-SW (Y7-199912) (Reference), P1-25/I2/SVB (Y7-207293) P1-32/I2/SVB (Y7-207314), P1-40/I2/SVB (Y7-199909), P1-25/I2/SVB-SW (Y7-207294), P1-32/I2/SVB-SW (Y7-207315) *[The product market is spread globally. Different scenarios are studied considering distribution in UK and outside Europe and separate extrapolation factors are given in this PEP considering Europe market as reference]
Functional unit	"Turn off all or part of an installation by separating the installation or part of the installation of all electrical energy or earth, for safety reasons with a rated voltage 690V, and rated current 40A, ensuring isolation characterised by a rated voltage 6000 V, and with IP Rating of IP65, according to the appropriate use scenario, and during the reference service life of the product of 20 years."
Company information	Eaton Production International GmbH Claylands Avenue, Dukeries Industrial Estate, S81 7DJ, United Kingdom

Constituent Materials	Constituent Materials							
Reference product mass	5.43E-01 kg (With packaging)							
Category PEP Material	Materials	Mass (kg)	Percentage (%)					
Plastics	Polycarbonate	2.46E-01	45.4%					
Plastics	Polyamide	1.28E-01	23.6%					
Others	Cardboard	8.46E-02	15.6%					
Metals	Stainless Steel	2.97E-02	5.5%					
Metals	Brass Ingot	2.19E-02	4.0%					
Plastics	Acrylonitrile butadiene styrene	1.70E-02	3.1%					
Others	Paper	5.00E-03	0.9%					
Plastics	Polybutylene terephthalate	3.70E-03	0.7%					
Metals	Silver	1.72E-03	0.3%					
Metals	Steel Wire Rod	1.60E-03	0.3%					
Others	Label	1.25E-03	0.2%					
Plastics	Ethylene vinyl acetate	8.00E-04	0.1%					
Plastics	Silicon Rubber	4.67E-04	0.1%					
Plastics	Polyethylene low density	4.53E-04	0.1%					
	Total	5.43E-01	100.0%					

Substance Assessment

The representative product is compliant with the EU-RoHS Directive (2011/65/EU) without exemption and the product doesn't contain any Substance-of-Very-High-Concern (SVHC) on the Candidate List of the EU-REACH Regulation (1907/2006/EC).

Additional Envir	onmental Information
Manufacturing	The reference product is assembled at an Eaton plant in United Kingdom, holding management system
Manufacturing	certifications according to ISO 14001 standards.
Distribution	Eaton is committed to minimizing weight and volume of product and packaging with focus to optimize
Distribution	transport efficiency.
Installation	The installation process does not require any energy consumption and there is no waste other than
mstanation	the obsolete product packaging generated during this step.
Use	The product requires energy consumption during operation.
	The recyclability rate of the overall product is 90% if it is properly dismantled prior to shredding. The
End of life	rate is calculated based on "ECO'DEEE recyclability and recoverability calculation method" (version
	V1, 20 Sep. 2008 presented to the French Agency for Environment and Energy Management:
	ADEME).

Environmental Impacts

The calculation of the environmental impacts is the result of the Product's Life Cycle Analysis in accordance with ISO 14040/44, covering the entire lifecycle, i.e., "Cradle-to-Grave" including the following life cycle phases: production, distribution, installation, use and end of life.

System modelling was carried out using the commercial LCA software EIME v6.2 with database version CODDE-2024-06-04.

Indicators Set: PEF EF 3.1 (Compliance: PEP ed.4, EN15804+A2) v2.0

Manufacturing Phase	The product is assembled as well as packed at Eaton Production International GmbH, United Kingdom, plant.
	Energy model used: United Kingdom
Distribution	Distribution of the product in its packaging from Eaton's last logistics platform to the installation
Phase	place is considered in Europe.
Installation	Product is installed in Europe.
Phase	Treatment of packaging waste is considered in this phase as per country specific statistics given in
Filase	PSR. Energy model used: Europe
	Reference lifetime: 20 Years
	Usage profile: The product has power loss of 10.5W at full load condition.
Use Phase	For industrial and commercial applications under low voltage scenario considering 50% of the loading rate and 30% use time rate, total losses are 137.97 kWh over the 20 years. Product do not require any maintenance/replacement during useful life. Energy Model Used: Europe
End of life	Product is disposed with WEEE guidelines.
Phase	Energy model used: Europe
riiase	
	Module D is calculated according to PCR-ed4-EN-2021 09 06 based on the materials recycled and the
Module-D	modelled end-of-life scenario. It expresses the net benefits and loads beyond the boundaries of the
	system and are not to be included in the life cycle totals.

Environmental Impact Indicators: Mandatory

Mandatory environmental impact indicators	Units	Sum	Manufacturi ng	Distribution	Installation	Use (Only B6)	End of life
Depletion of abiotic resources – elements (ADP-e)	kg SB eq.	2.46E-03	2.44E-03	5.10E-09	4.69E-09	1.72E-05	3.95E-06
Depletion of abiotic resources - fossil fuels (ADP-f)	MJ	1.31E+03	6.98E+01	1.81E+00	1.00E+00	1.23E+03	1.14E+01
Acidification (AP)	mole of H+ eq.	2.70E-01	1.79E-02	8.20E-04	3.11E-04	2.49E-01	2.20E-03
Freshwater eutrophication (EP-fw)	kg P eq.	3.42E-04	8.39E-05	4.86E-08	1.34E-06	1.28E-04	1.28E-04
Marine aquatic eutrophication (EP-m)	kg N eq.	3.47E-02	3.46E-03	3.84E-04	1.43E-04	3.03E-02	3.63E-04

Mandatory environmental impact indicators	Units	Sum	Manufacturi ng	Distribution	Installation	Use (Only B6)	End of life
Terrestrial eutrophication (EP-t)	mol N eq.	5.29E-01	3.19E-02	4.22E-03	9.59E-04	4.88E-01	4.35E-03
Climate change – total (GWP)	kg CO ₂ eq.	5.27E+01	3.23E+00	1.29E-01	2.59E-01	4.86E+01	4.10E-01
Climate change – biogenics (GWP-b)	kg CO ₂ eq.	1.71E-01	-6.90E-02	0.00E+00	1.46E-01	8.95E-02	4.67E-03
Climate change - fossil fuels (GWP-f)	kg CO ₂ eq.	5.25E+01	3.30E+00	1.29E-01	1.13E-01	4.85E+01	4.05E-01
Climate change - land use and land use transformation (GWP-lu)	kg CO ₂ eq.	3.55E-04	3.55E-04	0.00E+00	0.00E+00	0.00E+00	1.14E-07
Ozone depletion (ODP)	kg CFC- 11 eq.	4.22E-07	1.77E-07	1.98E-10	1.43E-09	2.36E-07	7.57E-09
Photochemical ozone formation (POCP)	kg NMVOC eq.	1.07E-01	8.94E-03	1.06E-03	2.24E-04	9.55E-02	1.12E-03
Water scarcity (WP)	m³ eq	5.06E+00	1.22E+00	4.92E-04	8.29E-03	3.73E+00	1.13E-01

Module D
-1.40E-02
-2.01E+00
6.50E-02
-2.08E+00
-3.13E-04
-1.00E-07
-4.41E-03
-8.93E-01

Inventory Flow Indicators: Mandatory

Inventory flow indicators	Units	Sum	Manufacturing	Distribution	Installation	Use (Only B6)	End of life	Module D
Use of renewable primary energy, excluding renewable primary energy resources used as raw materials	MJ	3.31E+02	5.33E+00	2.41E-03	1.37E-01	3.25E+02	8.22E-01	-1.21E+00
Use of renewable primary energy resources used as raw materials	MJ	2.50E+00	2.50E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	-1.31E+00
Total use of renewable primary energy resources (primary energy and primary energy resources used as raw materials)	MJ	3.34E+02	7.83E+00	2.41E-03	1.37E-01	3.25E+02	8.22E-01	-2.53E+00
Use of non-renewable primary energy, excluding non-renewable primary energy resources used as raw materials	MJ	1.30E+03	5.73E+01	1.81E+00	1.00E+00	1.23E+03	1.14E+01	-3.23E+01
Use of non-renewable primary energy resources used as raw materials	MJ	1.26E+01	1.26E+01	0.00E+00	0.00E+00	0.00E+00	0.00E+00	-1.05E+01
Total use of non-renewable primary energy resources (primary energy and primary energy resources used as raw materials)	MJ	1.31E+03	6.98E+01	1.81E+00	1.00E+00	1.23E+03	1.14E+01	-4.28E+01
Use of secondary materials	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Use of renewable secondary fuels	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Use of non-renewable secondary fuels	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Net use of fresh water	m³	1.19E-01	2.87E-02	1.14E-05	6.51E-04	8.75E-02	2.63E-03	-2.08E-02
Components for re-use	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Materials for recycling	kg	6.03E-01	1.12E-01	0.00E+00	7.37E-02	0.00E+00	4.17E-01	0.00E+00
Materials for energy recovery	kg	1.25E-02	4.61E-05	0.00E+00	8.23E-03	0.00E+00	4.25E-03	0.00E+00

Inventory flow indicators	Units	Sum	Manufacturing	Distribution	Installation	Use (Only B6)	End of life
Exported energy	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Hazardous waste disposed of	kg	1.32E+01	1.06E+01	0.00E+00	5.61E-03	2.13E+00	4.60E-01
Non-hazardous waste disposed of	kg	9.73E+00	1.35E+00	4.54E-03	3.64E-02	8.21E+00	1.22E-01
Radioactive waste disposed of	kg	2.51E-03	5.73E-04	3.24E-06	6.43E-06	1.88E-03	4.10E-05
Biogenic carbon content of the product	kg C	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Biogenic carbon content of the associated packaging	kg C	6.01E-02	6.01E-02	0.00E+00	0.00E+00	0.00E+00	0.00E+00

Module D
0.00E+00
-5.68E+00
-7.87E-01
-4.23E-04
0.00E+00
0.00E+00

Environmental Impact Indicators: Optional

Optional Environmental impact indicators	Units	Sum	Manufacturing	Distribution	Installation	Use (Only B6)	End of life
Ecotoxicity, fresh water	CTUe	1.20E+02	2.53E+01	8.48E-02	1.48E+00	9.19E+01	1.39E+00
Human toxicity, cancer effects	CTUh-C	8.55E-07	8.38E-07	2.28E-12	1.08E-08	6.11E-09	2.62E-10
Human toxicity, non-cancer effects	CTUh-nC	3.05E-07	1.48E-07	4.40E-11	3.20E-10	1.46E-07	1.05E-08
Ionizing radiation, human health	kBq U ²³⁵ eq.	7.86E+01	8.44E+00	3.15E-04	1.37E-02	6.99E+01	2.49E-01
Impacts related to land use/soil quality	No dimension	2.76E+00	1.14E+00	0.00E+00	2.95E-04	1.35E+00	2.73E-01
Emission of fine particles	Disease occurrence	2.20E-06	1.67E-07	6.67E-09	1.84E-09	2.01E-06	1.57E-08
Total use of primary energy during the life cycle	МЈ	1.65E+03	7.77E+01	1.81E+00	1.14E+00	1.55E+03	1.22E+01

Module D
-1.62E+01
-4.74E-07
-8.20E-08
-4.63E+00
-8.73E-01
-8.79E-08
-4.53E+01

To evaluate the environmental impact of other product covered by this PEP, multiply the impact figures by-

Multiplying Factors for Manufacturing, distribution, installation, End of Life and Module-D phase Phase (For EU market):

Part No.	Description	Extrapolation Factors for Manufacturing, distribution, installation, End of Life and Module-D phase
Y7-199912 (Reference)	P1-40/I2/SVB-SW	1.00
Y7-207293	P1-25/I2/SVB	1.00
Y7-207314	P1-32/I2/SVB	1.00
Y7-199909	P1-40/I2/SVB	1.00
Y7-207294	P1-25/I2/SVB-SW	1.00
Y7-207315	P1-32/I2/SVB-SW	1.00

Multiplying Factors for Use Phase (For EU market):

Part No.	Description	Extrapolation Factor for Use Phase				
Y7-199912 (Reference)	P1-40/I2/SVB-SW	1.00				
Y7-207293	P1-25/I2/SVB	0.31				
Y7-207314	P1-32/I2/SVB	0.51				

Part No.	Description	Extrapolation Factor for Use Phase
Y7-199909	P1-40/I2/SVB	1.00
Y7-207294	P1-25/I2/SVB-SW	0.31
Y7-207315	P1-32/I2/SVB-SW	0.51

Factors for Manufacturing, Distribution, Installation, End of Life and Module-D phase for different geographical regions

Product	Geographica I regions	Phases	ADP- e (kg Sb eq.)	ADP-f (MJ)	AP (mol H+ eq.)	EP-fw (kg P eq.)	EP-m (kg N eq.)	EP-t (mol N eq.)	GWP (kg CO2 eq.)	GWP- b (kg CO2 e q	GWP- f (kg CO2 e q)	GWP- lu (kg CO2 eq.)	ODP (kg CFC- 11 eq.)	POCP (kg NMV OC eq.)	WP (m3 eq.)
	Europe (Reference)	All Phase							1.00						
V7 400044	Vnited Y7-199914 Kingdom (Reference		1.00												
			0.29												
(Reference			0.88	0.95	0.96	1.00	0.99	1.01	0.99	0.98	1.00	1.00	1.00	1.00	0.98
,	Outside	Manufacturin g							1.00						
		Distribution	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
	Europe	Installation	1.22	1.22	7.00	1.23	3.56	3.55	1.34	1.00	1.34	1.00	1.14	3.63	1.17
		End of Life	0.49	0.58	0.62	0.02	0.33	0.65	0.67	0.96	0.28	1.00	0.78	0.60	0.16

Factors for use phase for different geographical regions

Product	Geographica I regions	ADP-e (kg Sb eq.)	ADP-f (MJ)	AP (mol H+ eq.)	EP-fw (kg P eq.)	EP-m (kg N eq.)	EP-t (mol N eq.)	GWP (kg CO2 eq.)	GWP-b (kg CO2 eq	GWP-f (kg CO2 eq)	GWP- lu (kg CO2 eq.)	ODP (kg CFC-11 eq.)	POCP (kg NMVO C eq.)	WP (m3 eq.)
	Europe (Reference)	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
	Germany	1.09	0.86	1.50	0.54	1.34	1.39	1.07	0.73	1.07	1.00	1.43	1.35	1.28
	UK	0.79	0.75	0.67	0.79	0.69	1.17	0.71	1.19	0.71	1.00	0.82	0.61	0.66
Y7-199912	Austria	1.65	0.23	0.43	0.01	0.40	0.63	0.37	0.65	0.37	1.00	0.37	0.36	1.10
(Reference)	Netherlands	0.79	0.77	0.80	0.18	0.95	0.98	1.14	1.33	1.14	1.00	1.01	0.94	0.92
(Nererence)	India	0.60	2.47	5.87	0.16	5.13	3.64	3.93	0.25	3.94	1.00	4.74	5.44	2.69
	Czech Republic	0.45	1.66	2.35	1.77	2.05	1.77	1.59	0.44	1.59	1.00	2.02	2.12	1.20
	Finland	0.73	0.86	0.91	1.59	0.68	1.42	0.39	0.61	0.39	1.00	0.71	0.56	0.54
	Denmark	0.83	0.35	1.16	0.04	0.98	1.66	0.56	0.90	0.56	1.00	1.30	0.86	0.58

Disclaimer

This Product Environmental Profile and its content is based on information available to us. It refers to the product at the date of issue. We make no express or implied representations or warranties with respect to the information contained herein.

Registration Number	EATO-00154-V01.01-EN	PCR-ed4-EN-2021 09 06					
Verifier accreditation Number	VH53	Supplemented by	PSR-0005-ed3.1-EN-2023 08 12				
Date of issue	06-2024	Information and reference documents	www.pep-ecopassport.org				
		Validity period	5 years				
Independent verification of	Independent verification of the declaration and data, in compliance with ISO 14025: 20						
Internal							
The PCR review was condu	ucted by a panel of experts cha	ired by Julie Orgelet					
(DDemain)							
PEPs are compliant with X	PEP						
The components of the pro	eco						
other program.	PASS						
Document complies with I	PORT _®						
Type III environmental dec							