



Part No.:Hi-05A3SYDAC-00Y

Outline Dimensions


19/04315-00

§ Standard 5mm diameter package.

Characters


§ High intensity.

ITEM	MATERIALS
Resin(Mold)	Epoxy
Lens Color Code	C Water Transparent
	T Colored Transparent
	D White Diffused
	E Colored Diffused
Lead Frame	Ag Plating Iron Alloy
Dice	InGaN

Absolute Maximum Ratings ($T_a=25^\circ\text{C}$)

Item	Symbol	Value	Unit
Power Dissipation	PD	100	mW
DC Forward Current	IF	30	mA
Pulsed Forward Current	IFP	100*	mA
Reverse Voltage	VR	5	V
Operating Temperature	Topr	-25 ~ +80	°C
Storage Temperature	Tstg	-40 ~ +100	°C
Soldering Temperature	Tsol	260for5sec ^Δ	°C

* Duty 1/10 Pulse Width 0.1ms Δ At the position of 4mm from the bottom of the package

Directive Characteristics ($T_a=25^\circ\text{C}$)Electrical-Optical Characteristics ($T_a=25^\circ\text{C}$)

Parameter	Symbol	Value			Unit	Test condition
		Min.	Typ.	Max.		
Forward Voltage	Vf	---	1.8	2.4	V	If=20mA
Luminous intensity	Iv	2500	4000	7000	mcd	If=20mA
Wavelength	X(λd)	---	588	594	(nm)	If=20mA
	y	---	---	---	---	If=20mA
Reverse Current	Ir	---	---	5	μA	Vr=5V
Viewing angle	2θ1/2	---	15	---	Deg	If=20mA
Spectral half bandwidth	Δλ	---	25	---	nm	If=20mA