


EXTRACELL

SPECIFICATION				PHOTO	
MODEL	LC-2282	NAME	CLASS 2 BATTERY CHARGER		
PART NO.		SPEC.	12V 2A		
Switch Power Supply; For 12V lead-acid battery or 12V GEL battery.					
I	INPUT PROPERTY				
	1	AC input voltage range	85Vac~264Vac	Universal	
	2	AC input voltage rating	100Vac~240Vac		
	3	AC input frequency	47Hz~63Hz		
	4	AC input current	0.6A@ 115Vac/0.36A @ 230Vac	Max. (RMS)	
	5	AC input power	40W	Max.	
	6	AC input static state current	50mA	Max. (RMS)	
	OUTPUT PROPERTY				
	1	DC Output voltage range	4~15Vdc		
	2	DC Output power	30W	Max.	
	3	Bulk charge current rating	2A @ 12Vdc	±10%	
	4	Bulk charge voltage rating	14.7Vdc	±0.3Vdc	
	5	Float charge voltage rating	13.2Vdc	±0.25Vdc	
	6	Float switching current	400mA	±150mA	
II	GENERAL CHARACTERISTICS				
	1	Efficiency	78% (Typical)	At Max. Load	
	2	Over load protection	<3A		
	3	Output low voltage protection	4V	±1V	
	3	Short circuit protection	Enable	Red LED Flashing	
	4	Reversed polarity connectors protection	Enable	Red LED Flashing	
	5	Operating temperature	0°C~40°C		
	6	Storage temperature	-30°C~85°C		
	7	Operating relative humidity	8%~90%		
8	Storage relative humidity	5%~95%			
III	INDICATOR STATUS				
	1	Green LED on	Float charge		
	2	Green LED Flashing	Power on & empty load		
	3	Red LED on	Bulk charge		
	3	Red LED Flashing	Short or Reversed polarity connector		

