

			CUSTOMER		ELCART	
			PRODUCT NO.		42/20460-00	

1800 ± 30MM

(1)

(2)

(3)

(4)

(5)

SIDE:A

SIDE:B

NOTE:

(1). Cable Wiring: 30AWG/9C F
 Jacket Material: PVC-65P OD: 4.0 ± 0.2mm
 Cable Colour: Beige
 Cable Printing: COMPUTER INTERFACE CABLE 300V 80°C

(2). Connector A: DB 9PIN Female Solder Type
 Insulation: Blue
 Contact: Gold Plated
 Shell: Fe, Nickel Plated

(3). Connector B: DB 9PIN Female Solder Type
 Insulation: Blue
 Contact: Gold Plated
 Shell: Fe, Nickel Plated

(4). Thumb Screw: 2.3*47mm Injection Molding

(5). Over Mold Colour: PVC-45P-Beige

(6). Parameter Settings: CT-8681FA
 1. Conductive Resistance: 4.0 ~ 8.0 Ω
 2. Insulative Resistance: 5M Ω (Min.)
 3. Hi-Pot: 200V/AC, DC, 1.5mA/I, 50Hz, 0.01s

(7). ALL COMPONENTS ARE RoHS COMPLIANT.

(8). 100% OPEN AND SHORT TEST

SIDE:A	SIDE:B
DB 9P F	DB 9P F
3	2 BLACK
2	3 BROWN
4	6 RED
6	4 ORANGE
7	8 YELLOW
8	7 GREEN
5	5 BLUE

PIN OUT: (6)

Jacket

Conductor

Core Wire

Ø4.0 ± 0.2MM

GENERAL TOLERANCES (UNLESS SPECIFIED)						
LENGTH: X. ± 1 .X ± 0.2 .XX ± 0.10			UNIT: mm	REV: 00		
ANGLE: X° ± 1° .X° ± 0° 30'			DRAWING	2014/06/25	S. P. NO.	NAME DB 9PIN F-DB 9PIN F
			CHECK		P. O. NO.	DWG. NO.
			APPROVE		SIZE	PAGE 1/1

00	NEW	2014/06/25
REV	DESCRIPTION	DATE