



Caratteristiche

Characteristics

Rg 213/U

Impedenza nominale	Characteristic impedance	50 Ohm
Tolleranza	Tolerance	± 3 Ohm
Capacità	Capacitance	98 pF/m
Velocità di propagazione	Velocity ratio	0,66
Attenuazione nominale	Nominal attenuation	
50 Mhz	50 Mhz	4,3 dB/100 m.
100 Mhz	100 Mhz	6,3 dB/100 m.
200 Mhz	200 Mhz	8,9 dB/100 m.
400 Mhz	400 Mhz	13,5 dB/100 m.
800 Mhz	800 Mhz	21,1 dB/100 m.
1000 Mhz	1000 Mhz	26,3 dB/100 m.
Conduttore	Conductor	7 x 0,75 CU
Dielettrico	Dielectric	PE
Diametro dielettrico	Dimensions of dielectric	7,25 mm.
Tolleranza	Tolerance	± 0,20 mm.
Schermo	Screen	CU
Percentuale di schermatura	Coverage of screen	>80%
Guaina	Sheath	PVC
Diametro guaina	Diameter of sheath	10,3 mm.
Tolleranza	Tolerance	± 0,30 mm.
Minimo raggio di curvatura	Minimum bending radius	100 mm.
Peso per 100 m.	Weight 100 m	14,5 Kg.

CW=Acciaio ramato-Copperweld

CA=Rame argentato-Silver plated copper

CU=Rame rosso-Copper

ST=Rame stagnato-Tin plated copper

F.CU=Lamina rame rosso-Copper foil

ALU=Lamina alluminio poliestere-Aluminium polyester foil

PE=Polietilene-Polyethylene

PEE=Polietilene espanso-Foam polyethylene

PE/A=Polietilene aria-Air polyethylene

PVC=Policloruro di vinile-Polyvinyl chloride