






Ground - 12 mm 0.472 in spacing



ZS25-PE



12 mm 0.472 in spacing



- rail contact non operator dependent, secured snap on or off the rail.
- Same profile as ZS25 for aligned marking and identical end section.

Description	Color	Type	Part Number	Pkg	Weight
ART. 25/02330-00				qty	(1 poe) g
Ground Screwless rail connection	Green-yellow 	XS25-PE	1SNK512150R0000	20	38.00

Connecting capacity		IEC	UL - CSA	Rail		TH 35-7.5, TH 35-15
1 conductor per clamp	Rigid: Solid/Stranded	0.5 ... 25 mm²	24 ... 3 AWG	Wire stripping length		13.5 mm 0.531 in
	Flexible without ferrule	0.5 ... 25 mm²				
	Flexible with non insulated ferrule	0.5 ... 16 mm²	24 ... 4 AWG			
	Flexible with insulated ferrule	0.5 ... 16 mm²	24 ... 8 AWG			
	Gauge	A6-B6				
				Tool		Flat screwdriver Ø 5.5 mm Ø 0.217 in
Rated cross section		16 mm²	3 AWG	Torque		1.8 Nm ± 0.2 15.9 lb.in ± 1.77
Maximum cross section		25 mm²				
Rated short-time withstand current (1s)		1920 A	3204 A			
Maximum short-time withstand current (1s)		3000 A				
Protection		IP20	NEMA 1			

The connecting capacity data for one Rigid, Solid/Stranded, or one Flexible conductor (when applicable) is a mandatory information required by IEC, UL and CSA standards (Copper conductors). All other data are provided as supplementary information only. For more details, please consult our CB, UL or CSA certificates and technical datasheet available on <http://www.TE.com>



Description				Color	Type	Part Number	Pkg qty	Weight (1 pce) g
1	End stops	10 mm	0.394 in	Dark grey 	BAM4	1SNK900001R0000	50	14.00
2	End sections	2.2 mm	0.067 in	Dark grey 	ES4	1SNK50591R0000	20	2.20
3	Circuit separators	3 mm	0.118 in	Dark grey 	CS-R1	1SNK900103R0000	20	5.20
4	Terminal block markers	Blank marker		White 	MG-CPM 13 41791	1SNB041791R0612	1680	0.27
		Blank card			MC812	1SNK160000R0000	22	10.00
					MC812PA	1SNK169999R0000	20	14.00
		Universal wire markers holder		Grey 	UMH	1SNK900611R0000	10	0.20

Some accessories such as jumper bars may modify the terminal block's ratings: Complete information available in the accessories section of the catalog.

Technical data valid for copper conductors only.