



Alternative ON - ON

Instantaneous ON - (ON)

	TYPE	Contact points	MODEL	LED		
4/6493 4/6490	Alternative	(Single blade) 3P	ON - (ON)	2.1V		
4/6440 4/6443	Instantaneous	(Single blade) 3P	ON - (ON)	20mA		
4/6503 4/6504	Alternative	(Single blade) 3P	ON - (ON)	10000H		
4/6452 4/6453	Instantaneous	(Single blade) 3P	ON - (ON)			
4/6494 4/6495	Alternative	(Double blade) 6P	ON - (ON)	6V	12V	28V
4/6442 4/6444	Instantaneous	(Double blade) 6P	ON - (ON)	65mA	50mA	24mA
4/6496 4/6497	Alternative	(Double blade) 6P	ON - (ON)	10,000H		
4/6454 4/6456	Instantaneous	(Double blade) 6P	ON - (ON)			

Specifications

Ambient temperature	Relative humidity	Operating voltage	Rated current	Contact resistance	Insulation resistance	Test voltage
-55 ~ +85°C	98% ,40°C	125VAC / 250VAC	3A / 1A	≤ 0.02 Ω	≥ 1000M Ω	1500v ~ 1
Actuating force	Life					
2 ~ 10N	100,000					