



UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN mm	
TOLERANCE	
DECIMALS	ANGULAR
X ± 0.5	± 1°
XX ± 0.25	
DO NOT SCALE DRAWING	
P/N	請參照附表
REV.	B

Lead "A"	Lead "B"	"A"	"B"	"C"
#18 UL1015 Red wire	#18 UL1015 Red wire	152.4±5 (6")	152.4±5 (6")	22.2

Specifications:

Applicable : For 3AG Fuse Type AGC, SFE, JSO and MFA

Voltage Rating : Max 250V

Current Rating : Max.7.5A

Insulating Body : PP / White Color

Contacts : Brass

Wire Size : 1.#18 UL1015 Red Wire

2. Insulation Overall Diameter : 2.75mm

1	Cologno M.se 16/11/2020	Primo rilascio	AUTORE : Boscolo
REV.	DATA	DESCRIZIONE REVISIONE	ART. 04/10558-00
			TIMBRO e FIRMA

ELCART DISTRIBUTION SPA via Michelangelo Buonarroti, 46 - 20093 Cologno Monzese (Milano) ITALY Tel. +39 02.25117310 Fax +39 02.25117610

sito internet: www.elcart.com e-mail: tecnico@elcart.it

La divulgazione dei dati contenuti in questa scheda è da ritenersi un servizio puramente informativo e non costituisce alcun vincolo da parte della Elcart in merito a prestazioni ed utilizzo del prodotto.
The divulgation of data contained on this technical sheet are exclusively for informational reasons and establish no link on behalf of Elcart regard to the performances and the use of the product.
La divulgacion de los datos contenidos en esta ficha son un servicio unicamente informativo y no constituyen ningun vinculo de parte de Elcart respecto a las prestaciones y uso del producto.