

Sao 174 - 17W



Scheda tecnica

1650lm

17W

Caratteristiche

Corpo	Alluminio	Body	Aluminium
Diffusore	90°	Diffuser	90°
Finitura	Verniciato bianco	Finishing	White painted
Installazione	Incasso fisso da interno	Installation	Fixed recessed interior

Sorgente

LED	SMD 5630 Samsung	LED	SMD 5630 Samsung
Watt	17 W	Watt	17 W
CRI	CRI 85	CRI	CRI 85
MacAdam	3	MacAdam	3

Dati elettrici

Alimentazione	220-240V	Power source	220-240V
Alimentatore	INCLUSO	Power supply	INCLUDED

Dati illuminotecnici

Durata utile	L70 B50=50.000h 25°C L80 B50=30.000h 25°C	Life time	L70 B50=50.000h 25°C L80 B50=30.000h 25°C
Stoccaggio	-10(min) + 60 (max)	Warehouse	-10(min) + 60 (max)
Funzionamento	-10(min) + 25 (max)	Functioning	-10(min) + 25 (max)
Grado IP	IP44	IP	IP44
IEC 62471	(RG0) Gruppo di rischio fotobiologico esente	IEC 62471	(RG0) Photobiological risk exempt

Lumen nominali:

3000 K / 1573 lm	3000 K / 1573 lm
4000 K / 1650 lm	4000 K / 1650 lm

Features

Body	Aluminium
Diffuser	90°
Finishing	White painted
Installation	Fixed recessed interior

Source

LED	SMD 5630 Samsung
Watt	17 W
CRI	CRI 85
MacAdam	3

Electrical data

Power source	220-240V
Power supply	INCLUDED

Photometric Details

Life time	L70 B50=50.000h 25°C L80 B50=30.000h 25°C
Warehouse	-10(min) + 60 (max)
Functioning	-10(min) + 25 (max)
IP	IP44
IEC 62471	(RG0) Photobiological risk exempt




Marchi e garanzie

Norme	Standards	IEC 62031	IEC 62717	IEC 61000-4-2
Marchio	Mark	CE		
Garanzia	Warranty	2 anni		

Markings and warranty

DISEGNO TECNICO:

Technical illustration mm size



CODICE D'ACQUISTO

Order code

cod. BASE	Watt Watt	Colore LED LED color
S174	-	
	17 Watt	17W
		Bianco caldo Warm white C
		Bianco neutro Natural white N