

PORTA A VETRI, 800X800

CATALOG NUMBER

ADCS08080



É possibile visionare i componenti elettrici mentre la porta è chiusa, ciò impedisce l'accesso al personale non autorizzato e mantiene la protezione dell'ingresso.

FEATURES

Descrizione: Inserita al posto della porta standard, fornisce una chiara visione dei componenti installati all'interno. Permette il montaggio di qualsiasi tipo di chiusura.

Materiale: 1.5 mm acciaio inox AISI 304, 2 mm per cassette con altezza o larghezza pari a 600 mm o maggiore, e vetro di sicurezza trasparente da 4 mm.

Finitura: Acciaio inox pre satinato 400.

Protezione: Conforme a IP 55 | TYPE 12, 13, IK 07.

Quantità nell'imballaggio: 1 pezzo.

Glazed enclosure door for stainless steel wall mounted enclosures

The glazed door allows the electrical components to be seen while the enclosure's door is closed

The user can monitor the status of the components without the need for opening the enclosure's door maintaining the ingress protection

Note: * 3 point espagnolette locking. Not suitable for AFS

PRODUCT ATTRIBUTES

Height: 800 mm

Width: 800 mm

Material: Stainless Steel 304

Finish: Brushed

Color: Unpainted

Thickness: 1.5 mm

Latch Quantity: 2

Window Size: 659 x 643 mm

ADDITIONAL PRODUCT DETAILS

* Serratura a cariglione su 3 punti. Non adatto per AFS.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



nVent.com

Our powerful portfolio of brands:

TRACER

CADDY ERICO HOFFMAN RAYCHEM SCHROFF