PASSACAVO MODUL. INVERT., 1/4

CATALOG NUMBER

CCFO14

Il sistema di passacavi modulare CCFO è rapido, sicuro e versatile, si monta dall'esterno e fornisce guarnizioni sicure e serracavi per cavi pre-assemblati e non assemblati, con o senza connettori. Il sistema di passacavi è gestito dall'esterno della cassa.

INDUSTRY STANDARDS

UL 508A Component Recognized; Type 1, 12, 4X (indoor only); File No. E61997

UL94 V-0 Flammability

NEMA Type 1, 12, 4X (indoor only)

CE

IP66

FEATURES

Fornitura: Telaio, copertura protetta + inserto per CCFGS

Descrizione: CCFO è un sistema di passacavi invertito che consente l'assemblaggio completo dall'esterno della cassa. È realizzato in robusta plastica rinforzata con fibra di vetro. La guarnizione in gomma contribuisce a garantire una tenuta ottimale con protezione IP66. Il sistema CCFI viene fornito con inserti predisposti per adattarsi a piccoli anelli di tenuta (CCFGS). Gli anelli di tenuta CCFG devono essere ordinati separatamente. I divisori CCFD possono essere acquistati separatamente se è necessaria una configurazione diversa.

Finitura: Nero

Infiammabilità: UL94 V-0

Materiale: Poliammide 6,6 / TPE

Quantità nell'imballaggio: 1 pz

Protezione: IP66, NEMA 1, 4x, 12 (solo per uso in ambienti interni)

Resistenza alla temperatura: Da -40 °C a +120 °C

PRODUCT ATTRIBUTES

Cable Entry Quantity: 4

Cutout Size: 46x36 mm

Height: 64 mm

Width: 81 mm

Depth: 24.2 mm

Material: Plastic

Finish: Untreated

Color: Black

Operating Temperature: −40 to 120 °C

Weight: 0.1 kg

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2024 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.