

PRESSACAVO A DOPPIA TENUTA M40

CATALOG NUMBER

CED40



Il passacavo in gomma è facile da montare e i cavi e i tubi possono essere tirati facilmente senza attrezzi, assicurando il mantenimento del grado di protezione della cassa.

FEATURES

Descrizione: La guarnizione di gomma è molto semplice da usare. L'installazione non richiede attrezzi, che a sua volta significa costo del lavoro più basso. La membrana "pushout" è un sigillo permanente fino a quando non è penetrata da un cavo o un tubo. Adatto per fori in materiali da 0,5 a 4 mm di spessore.

Materiale: EPDM, senza alogeni.

Resistenza alla temperatura: -40°C a +110°C.

Finitura: RAL 7035.

Protezione: IP 67.

The protection degree is maintained if the outside layer fails due to damage or external circumstances

The double layer sock is the optimal solution if the outside layer is exposed to external circumstances such as high pressure water

A potential disadvantage of the double layer however is that cables only pass through straight

A single layer sock is available (CES) to allow cable passing through with an angle but the protection degree might be at risk if this single layer fails

Material: EPDM, halogen free

Temperature resistance: -40 °C to +110 °C

PRODUCT ATTRIBUTES

Height: 48.5 mm

Width: 48.5 mm

Depth: 29.5 mm

Material: EPDM

Finish: Smooth

Color: Light Gray

Color Code: RAL 7035

Height: 21.7 mm

Diameter: 48.5 mm

Cable Diameter Range: 19 – 28 mm

Hole Diameter: 40 mm

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



nVent.com

TRACER

Our powerful portfolio of brands:

CADDY ERICO HOFFMAN RAYCHEM SCHROFF