

PRESSACAVO TENUTA SEMPLICE M16

CATALOG NUMBER

CES16



Il passacavo in gomma è facile da montare, e i cavi e i tubi possono essere tirati facilmente con un'inclinazione senza attrezzi, assicurando il mantenimento del grado di protezione della cassa.

FEATURES

Descrizione: Semplice anello di tenuta realizzati in un materiale gommoso. L'installazione non richiede attrezzi. La membrana "pushout" è un sigillo permanente fino a quando non è penetrata da un cavo o un tubo, e avete sempre una apertura circolare e il periodo garantito. E 'dotato di un calzino che chiude stretto intorno al cavo e consente di spostarla in giro come un "joy-stick" in apertura senza mettere in pericolo l'IP, quindi funziona molto bene con i cavi che passano attraverso un angolo. Adatto per fori in materiali da 0,5 a 4,5 mm di spessore.

Materiale: TPE (elastomero termoplastico), senza alogeni.

Resistenza alla temperatura: -50°C a +125°C.

Finitura: RAL 7035.

Protezione: IP 67.

The installation does not require tools

The "pushout" membrane is a permanent seal until it is penetrated by a cable or pipe

It is equipped with a sock that closes tight around the cable and allows for it to be moved around like a "joy-stick" in the opening without endangering the IP, so it works extremely well with cables passing through at an angle

Suitable for holes in materials of 0.5 to 4.5 mm thickness

Temperature resistance: -50 °C to +125 °C

PRODUCT ATTRIBUTES

Height (H): 11 mm

Width (W): 24 mm

Depth (D): 24 mm

Material: Thermoplastic Elastomer

Finish: Smooth

Color: Light Gray

Color Code: RAL 7035


Height (h1): 4 mm

Size: M16 mm

Diameter: 23.5 mm

Cable Diameter Range: 5-10 mm

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.