

PRESSACAVO PLASTICA M12,100 PZ

CATALOG NUMBER

CPG12



La compressione di ogni cavo inserito in questo passacavo può essere regolata e fissata mediante un dado di bloccaggio, il che garantisce una protezione contro le deformazioni nonché un'elevata protezione dell'ingresso.

FEATURES

Descrizione: Pressacavo tradizionale. Conosciuto per la eccellente tenuta a trazione, fornendo elevata classe di protezione. Le ghiera in plastica per il fissaggio sono incluse nella fornitura.

Materiale: Corpo pressacavo in poliammide PA6, guarnizione in neoprene.

Resistenza alla temperatura: -20°C to +100°C.

Infiammabilità: V-2 according to UL94.

Finitura: RAL 7035.

Protezione: IP 66

PRODUCT ATTRIBUTES

Height: 31 mm

Width: 15 mm

Depth: 17 mm

Material: Polyamide 6; Neoprene

Finish: Smooth

Color: Light Gray

Color Code: RAL 7035

Thread Size: M12 x 1.5

Cable Size: 3 - 6.5

Package Quantity: 100

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation,

misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF
TRACER