VENTOLA A GRIGLIA EMC 480 M3/H

CATALOG NUMBER

EFE500R5

Questa ventola con filtro per montaggio verticale EMC, EFE, con grado di protezione IP 54, è facile da montare grazie al fissaggio a scatto. Poiché acqua e polvere non possono penetrare all'interno dell'unità attraverso il filtro, gli inutili tempi di inattività sono eliminati e, grazie all'affidabile motore della ventola, viene garantita una ventilazione costante. Le prestazioni EMC degli armadi specifici EMC sono garantite grazie a questa ventola con filtro.

INDUSTRY STANDARDS

cUL

CE UKCA

EAC

CE

GOST

UR

FEATURES

Descrizione: Ventilatori filtro EMC. Schermatura EMC speciale con maglie in acciaio inox che garantiscono un ottimo contatto con la superficie dell'armadio ed una lunga durata.
Approvazioni: CE, GOST, UR, cUL.
Materiale: Plastica, UL 94-V0. Schermatura EMC: maglie di contatto in acciao inox.
Quantità nell'imballaggio: 1 Ventilatore con filtro e sagoma/sezione di montaggio.
Material: Plastic, UL 94-V0; EMC screen: stainless steel, contact strips
Pack quantity: 1 fan with filter
The filter fan is reliable due to its high quality motor, as well as being easy to install
EMC performance is maintained when installed on an EMC enclosure
Component failure and unnecessary downtime is avoided as water, dust and electromagnetic interferences are prevented from entering the enclosure and the reliable motor ensures that there is constant ventilation
The click-in feature reduces the customer's labour cost due to the ease of installation
The filter fan should be installed together with at least one exhaust filter, EFAE
Voltage: 230 V AC, 50/60 Hz
Filter mat (EN779) G4
Bearing Type: Sleeve

PRODUCT ATTRIBUTES

Height: 320 mm
Width: 320 mm

Depth: 155 mm

Material: Plastic

Finish: Textured

Color: Light Gray

Nominal Voltage: 230 V

Frequency: 50/60 Hz

Power @ 50 Hz: 80 W

Power @ 60 Hz: 100 W

Airflow Volume: 480/480 (no filter), 370/370 (with filter) m^3/h

Filter Efficiency: 90 %

Service Life: L10 (40 C)(hy): 40.0

Noise Level: 54 dB

Enclosure Cutout: 292 x 292 mm

Connection Type: Spring Type

Nominal Current: .35/.45 A

Protection Fuse: 6 A

Weight: 3.85 kg

ADDITIONAL PRODUCT DETAILS

IP 55 a richiesta.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2024 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.