


RISCALDATORE VENTOLA 150W

CATALOG NUMBER

EHV150



Questo riscaldatore ventilato ad alte prestazioni, EHV, ha un'elevata capacità di riscaldamento. Utilizza una ventola per distribuire uniformemente il calore generato all'interno dell'armadio, evitando zone calde. Il fenomeno della condensazione dell'acqua è eliminato, anche quando la temperatura ambiente scende bruscamente.

INDUSTRY STANDARDS

cRUus_UL

CE

EAC

FEATURES

Descrizione: Riscaldatore ventilato ad eccellente risparmio di spazio per prevenire la condensazione. Il ventilatore favorisce la naturale convezione per una veloce distribuzione del calore in armadi voluminosi. Montaggio su barra DIN 35 mm (EN60715). Autoprotezione di sicurezza da surriscaldamento in caso di rottura del ventilatore

Elemento riscaldante: Cartuccia elevata efficienza.

Materiale: Plastica in conformità a UL 94 V-0 e pressofusione di alluminio.

Durata della ventola: 50.000 ore a 25 °C.

Temperatura operativa: -45 °C a +70 °C.

Connessione: Connettore a tre poli con terminali a vite da 2.5 mm².

Protezione: IP 20, Classe I (messa a terra).

Approvazioni: CE

Quantità nell'imballaggio: 1 pezzo.

Pack quantity: 1 piece

High performance fan heater with a high heating capacity

The large amount of heat generated by the optimised sized heater is distributed within the enclosure using forced air, produced by the heater's fan

When installed, water condensation will be avoided especially in situations when the ambient temperature dramatically drops

As the air will be distributed by the integrated fan, hot spots within the enclosure will be prevented

A thermostat with a normally closed contact, ETR or EFR, is recommended in order to control the heater

Voltage (V): 230 V AC 50/60 HZ

Protection: IP 20, Class I (earthed)

PRODUCT ATTRIBUTES

Height: 112 mm

Width: 81 mm

Depth: 47 mm

Material: Aluminum; Plastic

Finish: Powder Coated

Color: Gray

Heater Capacity: 150 W

Airflow: 35 m³/h

Weight: 0.55 kg

ADDITIONAL PRODUCT DETAILS

Tensione (V): 120 V AC su richiesta.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



nVent.com

Our powerful portfolio of brands:

TRACER

CADDY ERICO HOFFMAN RAYCHEM SCHROFF