

NIPPLO DA 6,00", F22: INOSSIDABILE PASSANTE 4X WW

CATALOG NUMBER

F44WN6SS



Feed-Through Stainless Nipples are used between adjacent wireway sections or fittings for adjusting wireway length. Connects to other wireway sections and fittings and protects wires and cables in frequently hosed down, very wet or highly corrosive applications.

FEATURES

Feed-Through Stainless Nipples are used between adjacent wireway sections or fittings for adjusting wireway length

Connects to other wireway sections and fittings and protects wires and cables in frequently hosed down, very wet or highly corrosive applications

PRODUCT ATTRIBUTES

Type: Nipple

Height: 102 mm

Width: 102 mm

Depth: 152 mm

Material: Stainless Steel 304

Finish: No. 2B

Color: Unpainted

Thickness: 1.59 mm

ADDITIONAL PRODUCT DETAILS

All dimensions are to outside surfaces. Allow .12 in. (3 mm) additional for gasket at joints. Dimension J is from intersection of center lines.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



[nVent.com](https://www.nVent.com)

Our powerful portfolio of brands:

CADDY ERICO HOFFMAN RAYCHEM SCHROFF

TRACER