

RACCORDO T, APERTURA SUPERIORE, F10: GUIDA CAVI 12 APERTA

CATALOG NUMBER

F66LTA



Lay-in Hinged Cover Tee Fitting with Top Opening is used when the covers of all three branches of the wireway run are open along the same side. Tee Fittings are finished with paint over plated surfaces.

INDUSTRY STANDARDS

Certified by Canadian Standards Association.

FEATURES

Lay-in Hinged Cover Tee Fitting with Top Opening is used when the covers of all three branches of the wireway run are open along the same side

Tee Fittings are finished with paint over plated surfaces

PRODUCT ATTRIBUTES

Туре: Тее	
Height: 152 mm	
Width: 152 mm	
Material: Mild Steel	
Finish: Galvanized; Powder Coated	
Color: Gray	
Color Code: ANSI 61	
Thickness: 1.9 mm	
Sealing Plate Type: Flat	
Sealing Plate Quantity: 2	

ADDITIONAL PRODUCT DETAILS

Ciascuna piastra di tenuta include anche una guarnizione e un set di viti per unire le sezioni.

Certificato dalla Canadian Standards Association.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands: **nVent.com** CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER

© 2024 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without notice.