

REFRIGERATORE VORTEX 820W, 184

CATALOG NUMBER

HT4640SS



Questo refrigeratore Vortex per alte temperature, HT, con grado di protezione IP 66, è facile da montare, non presenta parti in movimento e non richiede manutenzione. Oltre a svolgere la funzione di raffreddamento, serve anche a ridurre l'umidità relativa all'interno della cassa su cui è montato. Questo refrigeratore Vortex è una soluzione ideale per evitare il surriscaldamento all'interno dell'armadio in ambienti con temperatura fino a 93 °C, quali un'acciaieria.

INDUSTRY STANDARDS

CE

FEATURES

Descrizione: Compatto e affidabile sistema a basso costo per raffreddare e deumidificare contenitori. Produce l'aria fredda dall'aria compressa, senza parti in movimento. La facilità di montaggio attraverso un passaggio elettrico standard rende questa soluzione particolarmente adatta per essere installata, anche quando i contenitori sono già in campo. Per un funzionamento continuo del Vortex, l'umidità relativa all'interno della custodia è mantenuta al 45%, senza condensa umidità all'interno del contenitore (il contenitore deve essere chiuso). Adatto anche per temperature ambiente fino a 93 °C, i componenti interni sono in grado di sopportare queste alte temperature. Esso include un silenziatore per ridurre al minimo il rumore. I refrigeratori devono essere installati verticalmente per mantenere il grado di protezione.

Materiale: Tubo Vortex e coperchio esterno realizzati in acciaio inox.

Protezione: A seconda del tipo, fino a IP 66 | TYPE 4X.

Quantità nell'imballaggio: Refrigeratore Vortex con accessori di montaggio.

The coolers must be installed vertically to maintain the protection degree

Pack quantity: Vortex cooler with mounting accessories

High temperature vortex cooler, with no moving parts and a high IP 66 protection degree

The vortex cooler provides a maintenance free cooling solution which also reduces the relative humidity within the enclosure

The vortex cooler can be installed on the enclosure easily, in environments of up to 93°C, reducing the required installation time

The maintenance free cooling solution prevents unnecessary downtime

This reliable solution reduces the customer's labour cost due to the ease of installation

The vortex cooler will be a good thermal management solution for high temperature environments such as a steel mill

It is recommended to install a thermostat, BPT, as well as an air distribution kit, BPA

Cooling capacity is calculated with pressured air being 20°C and having 7-bar pressure

Silencer included: Yes; Low pressure relief valve: Yes; Instalation cut-out diam. (mm): 48

PRODUCT ATTRIBUTES

Height: 184 mm
Width: 63 mm
Depth: 63 mm
Material: Stainless Steel 304
Nominal Capacity Watts: 820 W
Finish: Brushed
Color: Unpainted
Weight: 2.3 kg

ADDITIONAL PRODUCT DETAILS

La capacità di raffreddamento è calcolata con aria pressurizzata di 20 °C e con una pressione di 7 bar.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF
TRACER