PLUG-IN BUSBAR, 2000

CATALOG NUMBER

MSBS41420



This plug-in busbar, MSBS, can withstand a rated current up to 1400A, and has been tested according to IEC 61439. It is a flexible, easy to mount solution.

FEATURES

Descrizione: Vertical busbar to build up the plug-in system. The MSBS bars are fixed in the MSVH supports with standard bolts, washers and nuts. The rated current can be increased up to 2 x 1400A if the incoming connetion is in the middle.

Materiale: Tin plated aluminium.

Fornitura: 4 pieces of busbars.

PRODUCT ATTRIBUTES

Height: 2000 mm

Width: 40 mm

Depth: 82 mm

Material: Aluminum

Finish: Mill

Color: Unpainted

Mounting Plate Height: 1772 mm

ADDITIONAL PRODUCT DETAILS

*In: Rated current. *Icw: Rated short-time withstand current.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2024 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.