

ZOCCOLO INTERRATO, 1000X800X400

CATALOG NUMBER

PGM10184



I cavi possono essere facilmente instradati attraverso lo zoccolo a terra che, essendo montato sottoterra, ne consente la canalizzazione e quindi, un collegamento più rapido.

FEATURES

Descrizione: Zoccolo per fondazione a terra dell'altezza di 1000 mm. Profondità di scavo: 700-950 mm.

Materiale: 2 mm acciaio elettrozincato.

Finitura: Rivestimento a polvere in poliestere RAL 7035.

Quantità nell'imballaggio: 1 kit zoccolo da fondazione a terra.

Outdoor aluminum EKOM enclosures can be easily installed in the field thanks to the installation depth of the ground plinth

Cables that are channelled underground can be wired much quicker than if they had to be brought to the surface first.

For the installation of UDP polyester modular wall mounted enclosures in the base is required the adaptor frame UAF

PRODUCT ATTRIBUTES

Height: 1000 mm

Width: 1800 mm

Depth: 400 mm

Material: Galvanized Steel

Finish: Galvanized

Color: Light Gray

Color Code: RAL 7035

Thickness: 2 mm

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



[nVent.com](https://www.nVent.com)

Our powerful portfolio of brands:

CADDY ERICO HOFFMAN RAYCHEM SCHROFF

TRACER