

Sezione dritta da 24", F22: Inossidabile passante 4X WW

CODICE A CATALOGO

F44W24SS



Feed-Through Stainless Steel Hinged-Cover, Type 4X Straight Sections are used for enclosing wire and cable in wireway runs. Its water-proof and stainless steel features makes it suitable for frequently hosed down, very wet or highly corrosive applications. The traditional closed-loop design has an opening on one side for easy access to wires and cables. Sections are available in lengths from 12 inch to 120 inch.

STANDARD INDUSTRIALI

Certified by Canadian Standards Association.

CARATTERISTICHE

Feed-Through Stainless Steel Hinged-Cover, Type 4X Straight Sections are used for enclosing wire and cable in wireway runs

Its water-proof and stainless steel features makes it suitable for frequently hosed down, very wet or highly corrosive applications

The traditional closed-loop design has an opening on one side for easy access to wires and cables

Sections are available in lengths from 12 inch to 120 inch

For modification and customization, Type 316 stainless steel covers and bodies available upon request

ATTRIBUTI DEL PRODOTTO

Tipo: Sezione diritta

Altezza: 102mm

Larghezza: 102mm

Profondità: 610mm

Materiale: Acciaio inossidabile 304

Finitura: N. 2B

Spessore: 1.59mm

INFORMAZIONI DI PRODOTTO AGGIUNTIVE

All dimensions are to outside surfaces. Allow .12 in. (3 mm) additional for gasket at joints.

AVVERTIMENTO

I prodotti nVent devono essere installati e utilizzati solo come indicato nelle schede istruzioni e nei materiali di formazione di nVent. Le schede istruzioni sono disponibili su www.nvent.com e presso il vostro rappresentante del servizio clienti nVent. Un'installazione scorretta, un uso improprio, un'applicazione errata o qualsiasi altro mancato rispetto completo delle istruzioni e degli avvertimenti di nVent può causare malfunzionamenti del prodotto, danni alla proprietà, gravi lesioni personali e morte e/o annullare la vostra garanzia.



Il nostro straordinario portafoglio di marchi:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE