


Supporto post. busbar, 2200

CODICE A CATALOGO

MSVH2200



These vertical plug-in distribution busbar supports, MSVH, should be mounted on the enclosure behind the plug-in cover. They are available of the shelf and tested according to IEC 61439.

CARATTERISTICHE

Descrizione: Busbar supports up to 1600A to be mounted vertically behind the plug-in compartments. Rated short-time withstand current up to 35KA with rear supports and up to 50KA with rear and front supports. Mounts to the vertical profiles included in the rear cover plate for plugin sections MSSB.

Materiale: Polycarbonate reinforced with 10% of glass material.

Fornitura: 4 busbar support with mounting material.

The supports should be mounted onto the plug-in system vertical profiles (MSSB)

Plug-in busbars (MSBS), must be used in conjunction with these supports

Busbar supports up to 1600A to be mounted vertically behind the plug-in compartments

Rated short-time withstand current up to 35KA with rear supports and up to 50KA with rear and front supports

Mounts to the vertical profiles included in the rear cover plate for plugin sections MSSB

Delivery: 4 busbar support with mounting material

ATTRIBUTI DEL PRODOTTO

Altezza: 40mm

Larghezza: 482mm

Profondità: 45mm

Materiale della cassa: Lamiera d'acciaio

Famiglia di prodotti: Supporto libero

Materiale: Policarbonato

Finitura: Uniforma

Colore: Grigio

Spessore: 3.5mm

Corrente massima: 1600A

Corrente di tenuta a breve termine (Icw) 1s: 35kA

Quantità nella confezione: 8

INFORMAZIONI DI PRODOTTO AGGIUNTIVE

*In: Rated current. *Ick: Rated short-time withstand current.

AVVERTIMENTO

I prodotti nVent devono essere installati e utilizzati solo come indicato nelle schede istruzioni e nei materiali di formazione di nVent. Le schede istruzioni sono disponibili su www.nvent.com e presso il vostro rappresentante del servizio clienti nVent. Un'installazione scorretta, un uso improprio, un'applicazione errata o qualsiasi altro mancato rispetto completo delle istruzioni e degli avvertimenti di nVent può causare malfunzionamenti del prodotto, danni alla proprietà, gravi lesioni personali e morte e/o annullare la vostra garanzia.



Il nostro straordinario portafoglio di marchi:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE