



**DESCRIPTION** Crimping cable lug for termination of extruded cables up to 36 kV, for copper conductors.

**PRODUCT RANGE**

Section	Medium Voltage
Series	CMMT

**DIMENSIONAL INFORMATION**

Metel Code	Cross-section	F	L <sub>1</sub>	L <sub>2</sub>	D <sub>2</sub>
CM2535	mm <sup>2</sup> 25	mm 12	38	17.5	7
CM3040	mm <sup>2</sup> 35	mm 12	44	23	9
CM0050	mm <sup>2</sup> 50	mm 12	48	25	10
CM7080	mm <sup>2</sup> 70	mm 12	53	30	12
CM9510	mm <sup>2</sup> 95	mm 12	60.5	34	13.7
CM0120	mm <sup>2</sup> 120	mm 12	63	38	15.2
CM0150	mm <sup>2</sup> 150	mm 12	70	42	16.7
CM0185	mm <sup>2</sup> 185	mm 12	83	48	19.2
CM0240	mm <sup>2</sup> 240	mm 14	93	53	21.2
CM0300	mm <sup>2</sup> 300	mm 14	94	59	23.7
CM0500	mm <sup>2</sup> 500	mm 18	132	75	30,3

**PHYSICAL INFORMATION**

Material	Tinned copper
Halogen Free	(F), (Cl), (Br), (I), (At) Yes
Lead-Free	Pb Yes

**TECHNICAL INFORMATION**

Technology	Crimping
Copper conductor	Yes
Aluminum conductor	No
Necessary crimping tools	Yes
Suitable for multiple sections	No
Internal lubricant	Yes

**PRODUCT COMPLIANCE**

Certificates	n.a.
Reference standards	n.a.
Compliance	n.a.
Fire behavior	n.a.
ETIM classification	Version 7.0 EC001059



SAFETY INFORMATION	
Toxic product	No
Dangerous product	No
CLP Compliance (Regulation 1272/2008/EC)	n.a.

  

LOGISTIC INFORMATION	
HS code	85359000
Country of Origin	Italy

**NOTE**

This information and our technical indications correspond to our knowledge and experience without, however, constituting our warranty in relation to the final results or liabilities arising from any legal relationship. Given the multiplicity of materials, conditions of handling and storage, as well as production and usage conditions, all the information and indications mentioned above must be verified in advance by the user based on their specific circumstances of use.