



DESCRIPTION


IP68 re-enterable non-toxic gel-insulated joint for straight connection of 0,6/1kV power cables with 3-pole spring-clamp terminal block included.

PRODUCT INFORMATION

Section	Low Voltage
Series	EVO [®]
Metel Code	EV102
Trade name	EVO 02
Kit content	Pre-filled gel device, spring-clamp terminal block, instructions

DIMENSIONS

Length (L)	mm	80
Width (W)	mm	35
Height (H)	mm	28



CONNECTION INFORMATION

Straight connection	Yes
Branch connection	No
Technology	Gel
Installation	Overhead, in conduct, underground, in cable duct, temporary and permanent submersion
Number of cores (max)	3
Cable section (min – max)	(Flexible) mm ² 1,5 ... 2,5
Cable diameter (min – max)	mm 10 ... 13

CABLE INFORMATION

Insulation Degree	kV	0,6/1
Copper conductor		Yes
Aluminum conductor		Yes
Shield		n.a.
Armor		Optional – available separately

CONNECTOR INFORMATION

Connector included	Yes	
Connector type	Spring-clamp terminal block	
Connector material	Chromed steel	
Pre-insulated connector	Yes	
Connector insulation material	PA	
Rated voltage	kV	0,6/1
Rated current	A	-
Number of poles	3	
Clamping technology	Spring-clamp	
Copper conductor	Yes	
Aluminum conductor	Yes	
Copper/aluminum connection	Yes	

Special tools for clamping	No
Screws maintenance	No

SHELL INFORMATION

Material	Polypropylene (PP)
Dielectric Strength	kV/mm > 20
Colour	Black
Operating temperature (min – max).	°C - 20 ... + 90
Self-extinguishing	UL94 V2
Halogen Free	(F), (Cl), (Br), (I), (At) Yes
Lead Free	Pb Yes
UV Resistant	Yes
Innovative snap-closing system	Yes
Core separator	No
Strain Relief System (SRS)	No

INSULATION INFORMATION

Material	Silicone gel
Dielectric Strength	kV/mm 27
Colour	Transparent
Re-enterable	Yes
Non-toxic	Yes
Self-extinguishing	UL94 HB
Halogen Free	(F), (Cl), (Br), (I), (At) Yes
Lead Free	Pb Yes
Shelf life	Unlimited

PRODUCT COMPLIANCE

Certifications	200032822UDI-NSR R01		100180v2
Reference standards	CEI EN 50393	CEI EN 60529	CEI EN 60695-2-11
	CEI 20-37/4	CEI 20-37/2-1	
Conformity	Low Voltage Directive 2014/35/UE (LVD) Directive 2011/65/EU (RoHS 2) and 2015/863/UE (RoHS 3)		
Fire resistance	Self-extinguishing Low smoke and toxic gases emissions		
CE mark	Yes		
Double insulation	Yes		
Protection degree	IP	68	
ETIM Classification	Ver. 7.0	EC001169	

SAFETY INFORMATION

Harmful product	No
Dangerous product	No
CLP Compliant (Regulation 1272/2008/CE)	n.a.

INFORMAZIONI LOGISTICHE

Blister	pc	1	Barcode	EAN 13	8053323905486
	pc	1	Dimensions (L x W x H)	m	0,200 x 0,080 x 0,035
	pc	1	Weight	kg	0,070
Box	pcs	12	Barcode	EAN 13	8053323906179
	pcs	12	Dimensions (L x W x H)	m	0,240 x 0,200 x 0,120
	pcs	12	Weight	kg	0,960
HS code	85369010				
Origin	Italy				

NOTE

These information and our technical indications correspond to our knowledge and experience without however constituting our guarantee in relation to the final results or responsibilities deriving from any legal relationship. In fact, considering the multiplicity of materials, handling and storage conditions, as well as production and use conditions, all the information and indications above must be previously verified by the user according to his specific circumstances of use.