

APPLICATIONS

- Connections of low voltage cables in junction boxes or overhead (e.g. lighting fixtures, ceilings) in residential buildings

FEATURES

- Clear polycarbonate body
- Brass contacts
- Galvanised steel screws with slotted head (from TBOX 15 to TBOX 100), or Phillips head (TBOX 160)
- Galvanized steel hex grub screws (TBOX 250, TBOX 360)
- Degree of protection IP20
- IMQ Certified – CE Marking



10-way terminal block

ref.	item	cross-section (mm ²)	rated voltage (V)	rated current (A)	pack. (pcs)	min. / mult. ord. qty (pcs)
TBOX015	TBOX 015	1.5	450	24	10	100
TBOX025	TBOX 025	2.5		24	10	100
TBOX040	TBOX 040	4		32	10	100
TBOX060	TBOX 060	6		41	10	100
TBOX100	TBOX 100	10	500	57	5	50
TBOX160	TBOX 160	16		76	5	50

number of allowed conductors		
2 *	3	4
conductor cross-section (mm ²)		
1.5	1	0.75
2.5	1.5	1
4	2.5	1.5
6	4	2.5
10	6	4
16	10	6

* Cross-section of two allowed conductors equals rated cross-section



1-way connectors

ref.	item	cross-section (mm ²)	rated voltage (V)	rated current (A)	pack. (pcs)	min. / mult. ord. qty (pcs)
TBOX250	TBOX 250	25	500	101	5	50
TBOX350	TBOX 350	35		125	5	50

number of allowed conductors		
2 *	3	4
conductor cross-section (mm ²)		
25	16	10
35	25	16



TAKE it fast

50 × TBOX® 10-way assorted terminal blocks

TOOL ALWAYS INCLUDED

ref.	kit contents	min. / mult. ord. qty (pk)
KT1067	TBOX 040 - 20 pcs TBOX 060 - 20 pcs TBOX 100 - 10 pcs + TOOL INCLUDED	10/5