



DESCRIPTION

Kit of three heat-shrink terminations for indoor applications for single core cables with extruded insulation up to 24 kV with copper wire or tape shield.

PRODUCT INFORMATION

Section	Medium Voltage
Series	TTMT-I
Metel code	TT244001
Article name	TTMT-24/400-I
Kit contents	Anti-tracking oversheets, stress-control tubes, sealing heat-shrink tapes, instructions

TERMINATION INFORMATION

Technology	Heat-shrink
Applications	Indoor
Insulation degree	kV 12/20
Max insulation voltage	kV 24
Number of cores	1
Conductor section (min – max)	(Flex) mm ² 300 ... 400
Physical lenght (L)	mm 450
Heat-shrink sheds	0
Lunghezza linee di fuga	mm 450
Oversheet mmaterial	Polyolefin
Oversheet color	Red
Dielectric strenght	kV/mm -
Operating temp. range (min – max).	°C - 20 ... + 90
Lugs	n.a.
Self-extinguishing feature	Yes
Halogen Free	(F), (Cl), (Br), (I), (At) n.d.
Lead Free	Pb Yes
UV Resistant	n.d.

CABLE INFORMATION

Nominal insulation degree	kV 12/20
Single core	Yes
Three core	No
Elicord	Yes
Copper conductor	Yes
Aluminium conductor	Yes
Copper wire screen	Yes
Copper tape screen	Yes
Aluminium tube screen	No

LUGS INFORMATION				
Included lug	Available separately			
Lug type	n.a.			
Lug material	n.a.			
Clamping type	n.a.			
Copper conductor	n.a.			
Aluminium conductor	n.a.			
PRODUCT COMPLIANCE				
Certifications	n.a.			
Homologation Letter	n.a.			
Enel table	n.a.			
Enel serial number	n.a.			
Reference standards	CENELEC HD 629.1 S2 CEI 20-62/1			
Comportamento al fuoco	n.d.			
Protection degree	IP	n.a.		
ETIM Classification	Ver. 7.0	EC000910		
SECURITY INFORMATION				
Harmful product	No			
Dangerous product	No			
CLP Compliant (Regulation 1272/2008/CE)	n.a.			
LOGISTIC INFORMATION				
Packaging	Barcode	1 pc	EAN 13	8033501686352
	Dimensions (L x W x H)	1 pc	m	0,47 x 0,13 x 0,10
	Weight	1 pc	kg	0,77
Custom code	85469010			
Origin	Italy			

NOTE

This information and our technical indications correspond to our knowledge and experience without however constituting our guarantee in relation to the final results or responsibilities deriving from any legal relationship. In fact, considering the multiplicity of materials, handling and storage conditions, as well as production and use conditions, all the information and indications above must be previously verified by the user according to his specific circumstances of use.