



4TRE35 180x75R

Y41-05 p

DATA SHEET

release. g - Revision 01-2016



Voltage	Frequency	Input Power	Input Current	Capacitor	Airflow	Rotation speed	Acoustic level	Direction rotation	Admissible Temperature
V	Hz	W	A	μF	m³/h	RPM	dBA		Min/Max
230	50	106	0,47	3,0	600	1115	56	R	-20°C / +70°C
230	60	115	0,51	2,5	590	1110	56	R	-20°C / +70°C
230	50				353 CFM				-4°F / 158°F
230	60				347 CFM				-4°F / 158°F

dBA : free blowing



NA : not applicable

ErP 2013

NA

ErP 2015

NA




Tested with ECOFIT housing

Description

- .Weight : 2,5 Kg
- .Ball bearing
- .Class F, thermally protected
- .IP44 protection depending on installation and position as per EN60034-5
- .G2.5 balancing
- .PP plastic impeller
- .Rotor : black paint

U1 = Blue
U2 = Black
Z = Brown
PE = Green/Yellow





4TRE35 180x75R

Y41-05 p

DATA SHEET

release. g - Revision 01-2016

Data in accordance
to ErP directive

Voltage	230	V
Frequency	50	Hz
Power	0,090	kW ⁽¹⁾
Airflow	367	m ³ /h ⁽¹⁾
Pressure	150	Pa ⁽¹⁾
Rotation speed	1289	RPM ⁽¹⁾
(1) at optimal efficiency point		

ErP directive (EU 2009/125/EC) not applicable :
Power at optimum energy efficiency point

Accessories

19012
19011
21194
16133

Measurement setup

Contact ECOFIT

Documents

Manuel d'utilisation
www.ecofit.com/site/normes

Operating and recycling manual
www.ecofit.com/anglais/normes



A041865
4RS935CN

