



4VREt35 300A


R10-36

DATA SHEET

release. e - Revision 10-2016



Voltage	Frequency	Input Power	Input Current	Capacitor	Airflow	Rotation speed	Acoustic level	Direction rotation	Admissible Temperature
V	Hz	W	A	μF	m³/h	RPM	dBA		Min/Max
400	50	84	0,21	-	1850	1295	57	R	-20°C / +60°C
400	60	91	0,19	-	2030	1410	59	R	-20°C / +70°C
400	50				1088 CFM				-4°F / 140°F
400	60				1194 CFM				-4°F / 158°F



dBA : free blowing



NA : not applicable

ErP 2013

NA

ErP 2015


NA



Tested with ECOFIT ring

Description

- .Weight : 2,5 Kg
- .Ball bearing
- .Insulation Class F
- .IP44 protection depending on installation and position as per EN60034-5
- .G6.3 balancing
- .Zinc coated impeller
- .Rotor and impeller : black paint



U = Black
V = Blue
W = Brown
PE = Green/yellow



4VREt35 300A

R10-36

DATA SHEET

release. e - Revision 10-2016



Data in accordance to ErP directive

Voltage	400	V
Frequency	50	Hz
Power	0,090	kW ⁽¹⁾
Airflow	1326	m³/h ⁽¹⁾
Pressure	46	Pa ⁽¹⁾
Rotation speed	1251	RPM ⁽¹⁾
(1) at optimal efficiency point		

ErP directive (EU 2009/125/EC) not applicable :
Power at optimum energy efficiency point

Accessories

-
-
39658
09172



Measurement setup

16086 VIROLE V300 RONDE

Documents

Manuel d'utilisation
www.ecofit.com/site/normes

Operating and recycling manual
www.ecofit.com/anglais/normes



A041865
4RT935CN